


SOLJET PRO III XJ-540 54" ECO-SOLVENT™ INKJET PRINTER SOLJET PRO III XJ-640 64" ECO-SOLVENT™ INKJET PRINTER SOLJET PRO III XJ-740 74" ECO-SOLVENT™ INKJET PRINTER









The PRO III XJ Series Brings Pure Print Performance to Center Stage

Available in 54", 64" and 74" models, the XJ features Roland Intelligent Pass Control[™], our innovative technology that combines advanced dot placement with precisely-controlled media movement to deliver richly saturated 6-color prints with virtually no banding at razor-sharp resolutions up to 1440 dpi.

Vibrant images that pop, crystal-clear details that sparkle, subtle gradients that blend without banding, spot colors that hit the target. That's the kind of performance you should be looking for in your printer.

It takes more than simply a great printer to make a great print. It takes every element – printer, inks, media and software – working in perfect harmony. It takes the Roland Color Matching System for true spot color matching. And it takes customer education and support that allows you to get the most out of every print. We call this Pure Print Performance[™], and we do it better than anyone.



Learn about the included VersaWorks RIP software at www.rolanddga.com/versaworks

"We need reliable, easy-to-use equipment with excellent output. The only way we can survive is to consistently produce outstanding work. Our SOLJET keeps us in business."

Sarah Naccarato, Iconography Studios, Los Alamitos, California Read the entire Iconography article at www.rolanddga.com/Iconography













SOLJET PRO III XJ ECO-SOLVENT™ INKJET PRINTERS

- Blazing print speeds up to 458 sqft/hr
- 54". 64" or 74" maximum media widths
- Roland Intelligent Pass Control™
- Advanced ECO-SOL MAX INK
 - > Available in 440 or 220 ml cartridges
 - > Bonds to both uncoated and coated media
 - > Vibrant water, scratch and UV resistant graphics
 - > 3-year outdoor durability without lamination*
 - > No special ventilation equipment required
- Vibrant 6-color CMYKLcLm printing
- Photorealistic printing up to 1440x1440 dpi
- Variable Droplet Technology for superb detail
- Roland VersaWorks RIP software included
 - > Roland Color System for precise spot color matching
 - > Manage up to four Roland printers on a network
 - > Variable Data Printing
 - > Supports print/cut applications for GX series cutters
 - > Estimates ink usage and print time

- Automated take-up system included
- Optional DU dryer system available
- Two-Year Trouble-Free Warranty**



SOLJET PRO III XJ-740

74" INKJET PRINTER (shown with optional DU system)

SOLJET PRO III XJ-640

64" INKJET PRINTER (shown with optional DU system)

SOLJET PRO III XJ-540 54" INKJET PRINTER







For prices as well as detailed features and specifications, visit www.rolanddga.com/xj.

SPECIFICATIONS		SOLJET PRO III XJ-540	SOLJET PRO III XJ-640	SOLJET PRO III XJ-740
Print resolution		Maximum 1440 dpi		
Maximum printing width		53-9/16 in. (1361 mm)	63-9/16 in. (1615 mm)	73-9/16 in. (1869 mm)
Acceptable media width		8-5/16 to 54 in. (212 to 1372 mm)	8-5/16 to 64 in. (212 to 1625 mm)	8-5/16 to 74 in. (212 to 1879 mm)
Maximum media roll weight		Maximum 66 lb. (30 kg)	Maximum 88 lb. (40 kg)	Maximum 103 lb. (47 kg)
Ink cartridges Type Capo Colo	acity		Roland ECO-SOL MAX INK 12 cartridges: 220 ml or 440 cc ± 5 ml 6 color (CMYKLcLm)	
Max. printing speed		441 sqft/hr (40.9 sqm/hr)	443 sqft/hr (41.2 sqm/hr)	458 sqft/hr (42.5 sqm/hr)
Interface		Ethernet (10 BASE-T / 100 BASE-TX, automatic switching)		
Power-saving function		Automatic sleep feature		
Power-supply		AC 100 to 120 V +/- 10% 50/60 Hz or AC 220 to 240 V +/- 10% 50/61 Hz, / 13 A (100 to 120 V) or 7 A (220 to 241V)		
Media heating system		User-selectable temperature from 86° to 122° (30-50°C)		
Power consumption		Printing mode: Approx. 1600 W / Standby mode: Approx. 47 W		
Dimensions (with stand)		106-1/8 [W] x 43-3/8 [D] x 49-5/8 [H] in.	116 [W] x 43-3/8 [D] x 49-5/8 [H] in.	124-7/8 [W] x 43-3/8 [D] x 49-5/8 [H] in.
		(2694 [W] x 1103 [D] x 1260 [H] mm)	(2948 [W] x 1103 [D] x 1260 [H] mm)	(3169 [W] x 1103 [D] x 1260 [H] mm)
Weight (with stand)		441 l b (200 kg)	469 lb (213 kg)	495 lb (225 kg)
Environment Powe Powe	er on er off	Temperature: 59-90°F (15-32°C); 68F (20C) or more recommended Humidity: 35-80% (no condensation) Temperature: 41-104°F (5-40°C) Humidity: 20-80%		

^{*} Outdoor durability is based on accelerated weather tests. Results may vary depending upon location and application. Dry times vary depending on specific media characteristics. Lamination may be required for some applications or environmental conditions.
**Registration within 60 days and continuous exclusive use of Roland Inks during the first two years of ownership is required to qualify for the free second year of limited warranty coverage. Additional Terms and Conditions apply. Specifications subject to change

Get social with us.













