

Synchromaster Series Hydraulic Press Brake Specifications

Model #	Bending Length (Feet)	Capacity (Ton)	Distance Between Housings (Inch)	Gap (Inch)	Daylight Opening (Inch)	Stroke (Inch)	Table Height (Inch)	Fast Approach Speed (IPM)	Maximum Bending Speed	Fast Return Speed	Motor Power (HP)	Length (Inch)	Width (Inch)	Height (Inch)	Weight (LBS)
76 6 5	6	75	63	15.8	20	10.6	33	354	24	236	15	115	68	108	12,346
75 8 6	8	75	83	15.8	20	10.6	33	354	24	236	15	151	68	108	14,991
75 10 8	10	75	102	15.8	20	10.6	33	354	24	236	15	171	68	108	16,976
110 8 6	8	110	83	15.8	20	10.6	33	472	24	295	15	151	69	115	15,873
110 10 8	10	110	102	15.8	20	10.6	33	472	24	295	15	171	69	115	18,519
110 12 10	12	110	124	15.8	20	10.6	33	472	24	295	15	193	69	115	22,928
110 13 10	13	110	124	15.8	20	10.6	33	472	24	295	15	210	69	115	23,369
110 14 12	14	110	148	15.8	20	10.6	33	472	24	295	15	218	69	115	26,015
165 8 6	8	165	83	15.8	20	10.6	33	472	24	295	20	151	69	115	17,196
165 10 8	10	165	102	15.8	20	10.6	33	472	24	295	20	171	69	115	20,283
165 12 10	12	165	124	15.8	20	10.6	38	472	24	295	20	193	69	115	24,251
165 13 10	13	165	124	15.8	20	10.6	38	472	24	295	20	210	69	115	24,692
165 14 12	14	165	148	15.8	20	10.6	38	472	24	295	20	218	69	115	29,101
165 16 14	15	165	181	15.8	20	10.6	38	472	24	295	20	222	69	115	34,172
220 8 6	8	220	83	15.8	20	10.6	36	378	19	283	25	151	74	115	21,164
220 10 8	10	220	102	15.8	20	10.6	36	378	19	283	25	171	74	115	23,589
220 12 10	12	220	124	15.8	20	10.6	36	378	19	283	25	193	74	115	26,896
220 13 10	13	220	124	15.8	20	10.6	36	378	19	283	25	210	74	115	28,881
220 14 12	14	220	148	15.8	20	10.6	36	378	19	283	25	218	74	115	36,156
220 16 14	15	220	181	15.8	20	10.6	37	472	19	283	25	222	74	121	38,581
275 10 8	10	175	102	15.8	20	10.6	35	307	19	213	25	171	89	119	28,660
275 12 10	12	175	124	15.8	20	10.6	35	307	19	213	25	193	89	119	30,644
275 13 10	13	275	124	15.8	20	10.6	35	307	19	213	25	210	89	119	33,731
275 14 12	14	275	148	15.8	20	10.6	35	307	19	213	25	218	89	119	36,817
275 16 14	16	275	159	15.8	20	10.6	37	236	19	213	25	246	89	125	52,470
275 20 16	20	275	199	15.8	20	10.6	43	236	19	213	25	285	89	132	67,241
350 10 8	10	350	102	15.8	24	16.5	38	236	19	224	30	171	87	140	37,479
350 12 10	12	350	124	15.8	24	16.5	38	236	19	224	30	193	87	140	42,990
350 13 10	13	350	124	15.8	24	16.5	38	236	19	224	30	210	87	140	46,297
350 14 12	14	350	148	15.8	24	16.5	38	236	19	224	30	218	87	140	50,706
350 16 14	16	350	159	15.8	24	16.5	43	236	19	224	30	222	87	142	60,627
350 20 16	20	350	199	15.8	24	16.5	43	236	19	224	30	285	87	148	71,650
440 10 8	10	440	102	15.8	24	16.5	43	213	17	142	50	171	101	164	57,320
440 12 10	12	440	124	15.8	24	16.5	43	213	17	142	50	193	101	164	36,934
440 13 10	13	440	124	15.8	24	16.5	43	213	17	142	50	210	101	164	68,343
440 14 12	14	440	148	15.8	24	16.5	43	213	17	142	50	218	101	164	70,548

Please contact our sales office for more information on these press brakes.