

## ALFRA ELECTRO-HYDRAULIC PUMP DSP-120

Compact electro-hydraulic pump, two-stage operation withholding function for single-action hydraulic cylinder.

### Technical data

Operating voltage:	230 V/50 Hz
Motor power:	0.4 kW
max. operating pressure:	700 bar
Flow rate 0 - 20 bar:	2.0 l/min
Flow rate 20 - 700 bar:	0.2 l/min
Tank volume:	1.2 l
Usable oil volume:	0.8 l
Weight approx.:	7.5 kg

### Prod.-No.

02025

Electro-hydraulic pump with accessories

Contents: 1 hydraulic cylinder SKP-1  
1 hydraulic hose 1.8 m  
1 draw bolt Ø 19.0 and 19.0 x 9.5 mm  
1 spacer sleeve set multi-part  
1 pre-drill Ø 11.0 mm  
1 hand switch

02027

Electro-hydraulic pump only, 220 V, with 1.8 m hydraulic hose, quick coupling and hand switch

Foot switch 2-pedal

02029

Hand switch

02030



Prod.-No. 02025

## ALFRA AIR-HYDRAULIC PUMP – LHP 700

Air-hydraulic pump for the operation of single-action hydraulic cylinders for whole punchers, cable cutters, presses or similar applications.

- Heavy-duty tank
- Tank venting filter
- Reduced noise levels
- Oil level indicator on tank
- Precise start-up under load possible
- Precise activation - the drain valve activated by the foot pedal allows precise lowering of the load.
- Hydraulic hose 2.0 m with quick coupling

### Technical data

max. operating pressure:	700 bar
(at a feed line pressure of 7 bar)	
Feed pressure/working range:	2.8 - 10 bar
Air connection:	1/4" thread
Flow rate depressurised:	1.0 l/min
Flow rate p max. (with 7 bar air):	0.1 l/min
Tank volume:	2.4 l
Usable oil volume:	2.1 l
Weight:	6.3 kg

### Prod.-No.

02140

Air-hydraulic pump



Prod.-No. 02140