

K25 - Series Scrubbers

	DUAL DISK		ORBITAL		CYLINDRICAL	
						
	28 in / 710 mm	32 in / 810 mm	24 in / 610 mm	28 in / 710 mm	26 in / 710 mm	30 in / 762 mm
Tank Material:	Poly 5/16" (7.9mm)					
Chassis Construction:	3/16" Steel (4.8mm) Powder Coated Steel					
Front Wheels (Diameter x Width):	(2x) 10" x 2.5" (25.4 x 6.4cm) - Black					
Rear Casters (Diameter x Width):	(2x) 2.5" x 1.38" (6.4 x 3.5cm) - Black					
Length x Width x Height:	62 x 33 x 39.5 in *					
Dimensions listed are for the largest width deck configuration and casters removed from the machine	157 x 84 x 100 cm					
Scrub Motor(s):	0.75 hp / 559 watts		1.5 hp / 1,100 watts		0.75 hp / 559 watts	
Brush RPM:	270 rpm		2,500 rpm		270 rpm	
System Voltage:	36 VDC					
Standard Battery:	150 ah WET					
Battery Run Time:**	Up to 4 Hours					
Charger:	120VAC / 60 Hz Input - 36VDC / 25 amp Output					
Traction Drive System:	0.75hp - All Gear / Sealed (559 watts)					
Solution Tank Capacity:	25 gal / 95 L					
Solution Flow / Filter:	0 - 0.75 GPM / Stainless Inline (0 - 2.8 LPM)					
Recovery Tank Capacity:	26 gal / 98 L					
Vacuum Motor:	0.8 hp / 36V / 3 Stage / 640 watts					
Vacuum Water Lift:	70" / 178 cm / 70 cfm					
Squeegee:	41 in (104 cm)					
Downpressure:	80 lbs	80 lbs	80 lbs	90 lbs	120 lbs	130 lbs
Sound Levels:**	75 dBA**					
Productivity - Theoretical***	28,000 ft2/hr 2,601 m2/hr	31,915 ft2/hr 2,965 m2/hr	24,000 ft2/hr 2,230 m2/hr	28,000 ft2/hr 2,601 m2/hr	27,027 ft2/hr 2,510 m2/hr	30,000 ft2/hr 2,787 m2/hr
Productivity - Practical***	13,000 ft2/hr 1,208 m2/hr	14,851 ft2/hr 1,380 m2/hr	11,143 ft2/hr 1,035 m2/hr	13,000 ft2/hr 1,208 m2/hr	12,526 ft2/hr 1,163 m2/hr	14,000 ft2/hr 1,300 m2/hr

Specifications subject to change without notice.



Location:
Kodiak Cleaning Equipment
1711 South Street
Racine, WI
53404

Phone:
262-833-4025

Email:
customerservice@kodiakequip.com
Website:
www.kodiakequip.com

*Hollow Run Times are based on continuous scrubbing run times, standard batteries, low down pressure and all options off.
**Decibel levels for 90a per ISO 11051 as recommended by the American Association of Cleaning Equipment Manufacturers & CSMA
***Productivity is based off of OSHA 2000 Cleaning Times