


easymount.

EM-A1600SH WIDE FORMAT LAMINATING SYSTEM

Easymount Air® is a revolutionary product in the wide format lamination & mounting market.



GREAT FOR USE IN

Sign makers

Foot pedal

Reverse mode

KEY FEATURES

and film

• **NEW** Swing-out arms for

Pneumatic air pressure

Variable speed control

Multilingual control panel

10m/33ft a minute 30mm/1¾6" mounting

easier loading of laminate

· Print finishers

IDEAL WHEN LAMINATING

- Posters, graphics and signs
- Mounting prints to board
- Pop-up displays
- Applying vinyls, tapes and adhesive films
- Outdoor signage and many more...

Design & Performance

The patented technology within the Easymount Air uses one of the most advanced concepts ever seen in a wide format laminator. Pneumatic air pressure controls the laminating rollers, allowing you to mount and laminate with incredible accuracy and speed.

This new technology allows the roller to adjust to the exact thickness and pressure required, giving faster production times. The pneumatic air allows the roller to float down; ensuring Foamex and fluted boards are not crushed. When the rollers achieve the correct board thickness, the roller can be locked in place to keep the required gap, making board feeding more accurate. Mechanical wedges, often used to lock the roller by other pneumatic systems, are not required.

Features

use an existing air supply

 Swing-out Arms for easier loading of laminate and vinyl

NEW Swing-out

arm for laminate

- · Solid heavy duty construction
- · Release liner take-up
- Adjustable rollers up to 30mm/13/16"
- Large rollers for even pressure
- · Handy reverse mechanism
- Foot pedal for controlled operation
 - Optional rear take-up unit

Specifications	EM-A1600SH
Laminating Speed (m/ft/min)	10m/33ft
Max. Width (mm/inches)	1600mm/63"
Mounting Thickness (mm/inches)	30mm/1 ³ / ₁₆ "
Roller Diameter (mm/inches)	130mm/5"
Laminating Temperature (°C/°F)	0-60°C/32-140°F
Control Panel	Digital
Pressure Adjustment	Pneumatic
Film Core (mm/inches)	77mm/3"
Power Supply AC (V–Hz)	220/240–50-60
Power Consumption (W)	1500
Overall Dimensions (mm/inches)	2190x650x1255mm/86x26x49"
Gross Machine Weight (Kg/lbs)	245Kg/540lbs
Warranty	1 year



Patented pneumatic rollers 'float' down and will not crush soft materials like Correx®.



Front mandrel swings-out for easier loading of vinyl



Rear mandrel swings-out for easier loading of laminate



