



CAPACITY LITERS _____		SHELL SIDE	JACKET/COIL SIDE																		
Design Pressure KG/cm2 _____																					
Design Temperature °C _____																					
Material _____		AISI 304	Carbon Steel																		
MIXER TYPE: CONTINUOUS SCREW TYPE MIXER																					
Cover type: _____	Installed power HP: 25																				
Shaft seal: _____	Shaft speed RPM: 5/142																				
ANCC or ISPESL certification: NOT	NOZZLE DIMENSIONS <table border="1"> <thead> <tr> <th>Pos</th> <th>Service</th> <th>Size inch.</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>Polymer powder feed</td> <td>12"x10"</td> </tr> <tr> <td>B</td> <td>Solvent inlet</td> <td>1"</td> </tr> <tr> <td>C</td> <td>Slurry outlet</td> <td>6"</td> </tr> <tr> <td>D</td> <td>Cooling water in/out</td> <td>1"</td> </tr> <tr> <td>E</td> <td></td> <td></td> </tr> </tbody> </table>			Pos	Service	Size inch.	A	Polymer powder feed	12"x10"	B	Solvent inlet	1"	C	Slurry outlet	6"	D	Cooling water in/out	1"	E		
Pos				Service	Size inch.																
A	Polymer powder feed	12"x10"																			
B	Solvent inlet	1"																			
C	Slurry outlet	6"																			
D	Cooling water in/out	1"																			
E																					
Availability in stock n° 01 units																					
MANUFACTURER : BAKER PERKINS 13"/8"	NOTE Capacity: approx 2000-8000 Kg/h																				
<input type="checkbox"/> USED <input type="checkbox"/> USED RECONDITIONED <input checked="" type="checkbox"/> UNUSED																					
WEIGHT (approx) Kg 6200																					