



FLANGING MACHINE

Technology leader - developed together with our customers

New revolutionary fully electric

F-420e

F-420e

Ø21.3 - 419.0 mm

Copper, CuNi, Carbon steel,

Stainless steel, Aluminium SS 5 mm, excluding small tubes

Hot forming for carbon steels up to 9 mm

380-440 V / 50/60 Hz - 3-phase/ 12 kW

Revolutionary - fully electric Flanging Machine

Takes the flanging technology to a whole new level

Globally the first of its kind, T-DRILL's revolutionary Flanging Machine F-420e, is by far the most advanced flanging machine on the market – implemented with entirely programmable servo technology.

T-DRILL F-420e guarantees the highest possible workpiece quality and repeatability, including the best quality-related software adjustments on the market. All adjustments by the

program – ensure the fastest set-up time, also when switching from one pipe dimension to another.

The machine is easily operated to achieve maximal quality with minimal operator effect. Also, maintenance is very easy (no hydraulics), including mainly cleaning and lubrication.

F-420e is suitable for malleable materials, such as copper, carbon steel, stainless steel, aluminium, pipe diameters up to 420 mm (16"), wall thickness up to 5 mm with cold forming, and 9 mm with hot forming (carbon steel).

Wall thickness Cold flanging of carbon- and stainless steels Flanging of copper alloys Hot flanging of carbon steels 7 6 5 4 3 2 1 21.3 26.9 33.7 42.4 48.3 60.3 76.1 88.9 101.6 114.3 141.3 168.3 219.1 273.0 323.7 355.6 406.4 16 Tube outer diameter (mm / inch)

The information included in this brochure is subject to revision without notice.

Key Features:

Technical data

Pipe to be flanged

Materials to be formed

Operating voltage/Power

Max. wall thickness

- Fully Electric: no hydraulics and pneumatics
- Process fully by the program & servo technology means excellent repeatability with minimal quality-related operator effect
- Modern, easy, and instructional user interface and touch screen
- Extended safety features and operations
- Safe induction heater option for hot forming
- Optimized process speed without prevalent temperature dependence
- Easy and fast set-up time for new products also when switching from one pipe dimension to another
- A stable, robust structure guarantees vibration-free operation
- Low energy consumption
- $0-90^{\circ}$ flaring programmatically without accessories
- Clamping force adjustable by the program
- Industry 4.0 ready

Cut costs - Improve quality - Increase profit

- + Cut workshop costs by eliminating the need for welding and X-raying
- + Precise and stable results, no risk of weld or braze fracture

DO IT WITH T-DRILL

- + No costly flange inventories or complex equipment needed
- + Fast installation with loose flanges, no bolthole positioning
- + Very easy to operate and practically maintenancefree with programmability
- + Hot & cold forming for long and bent pipes, smooth/grooved flanged surfaces

MANUFACTURER:



T-DRILL OY

Ampujantie 32 66400 Laihia, FINLAND Tel. +358 6 475 3333 sales@t-drill.fom

T-DRILL Industries Inc.

1740 Corporate Drive, Suite #820, Norcross, Georgia 30093 USA Tel. +1-770-925-0520, sales@t-drill.com www.t-drill.com

REPRESENTED BY: