

HD PULPER

Certification Sheet

VOITH, INC.

2620 E. Glendale

Appleton, WI 54915

Tel (414) 731-7724

Telefax (414) 731-0240

IDENTIFICATION	CUSTOMER <u>CROSS POINTE PAPER CORP.</u>	CUST. DESIGNATION <u>HD-18</u>
	ADDRESS (ORDER) <u>PARK FALLS, WI</u>	<u>HIGH CONSISTENCY PULPER NO. 2</u>
APPLICATION	ADDRESS (INSTALL) <u>SAME</u>	TYPE/SERIAL NO. (S)* <u>3346</u>
	CUST. ORDER NO. <u>85000015</u>	VOITH JOB NO. <u>Y92-8674</u>
MAT'L	CUST. EQUIP. NO. <u>EQ-103</u>	ORDER DATE <u>4-15-92</u>
	CONTROLS BY <u>CUSTOMER</u>	CONTROLS SERIAL NO.* <u></u>
DRIVE	CERTIFIED BY <u>ROBERT J. MATZ, P.E.</u>	TITLE <u>MANAGER OF ENGINEERING, S.P. DIV.</u>
	INSTALLATION DWG. <u>D23-130019</u>	STOCK <u>BALED WASTE LEDGER, CPO, MOW</u>
MOTOR	STOCK CONSISTENCY <u>14-16% BD</u>	pH <u></u> TEMP <u></u>
	DESIGN PRODUCTION RATE <u>76</u>	BDSTPD OPERATING MODE <u>BATCH</u>
OPTIONS	TANK BY <u>VOITH</u>	I.D. <u>141.75</u> I.H. <u>112.13</u> O.A.H. <u>126.00</u>
	OPER. LEVEL <u>75.25"</u>	CAP. AT OPER. LEVEL <u>636(18M³)FT³</u> CAP. FLOODED <u>924(26M³)FT³</u>
REMARKS	IMPELLER RPM <u>151</u>	EXTRACTION HOLE SIZE <u>N/A</u> BLADE TYPE <u>HD-18</u>
	EXTRACTION: <u>WITHOUT</u>	DUMP NOZZLE SIZE: <u>20.00</u> INCH.
FURNISHED ONLY IF MARKED	PULPING UNIT <u>316L/MS</u>	EXTRACTION PLATES <u>N/A</u> EXTRACTION CHAMBER <u>N/A</u>
	TANK <u>316L/MS</u>	
*ALWAYS SPECIFY UNIT SERIAL NO. WHEN ORDERING SPARE PARTS	REDUCER BY <u>VOITH</u>	MFG. <u>FALK</u> MODEL <u>214722-S</u> RATIO <u>11.55:1</u>
	LO-SPEED <u>151</u>	HI-SPEED <u>1800 (1750 FLS)</u> MECH. HP RATING <u>1197</u>
	COUPLING BY <u>VOITH</u>	MFG. <u>FALK</u> TYPE <u>TORUS</u> SIZE <u>1120WA21</u>
	MOTOR BORE <u>3.375</u> KW <u>.875 X .437 X 5.0</u>	RED. BORE <u>3.500</u> KW <u>.875 X .438 X 5.50</u>
	PULPER MOTOR BY <u>CUSTOMER</u>	HP <u>450</u> RPM <u>1800</u> FRAME <u>5011LL V</u> 460 PH <u>3</u> HZ <u>60</u>
	LUBE MOTOR BY <u>VOITH</u>	HP <u></u> RPM <u></u> FRAME <u>V</u> PH <u></u> HZ <u></u>
	[] CONTROL PANEL [] COUPLING GUARDS [] STEAM VALVES [] TOOLS	
	[] TANK MANWAY [] " DUMP VALVE [] TANK HOOD	