

Basic machine

Aebi MT750, EU6, 115 kW (156 PS), 6 cylinders

Speed / drive

Speed limit 85 km / h, 7.5 t

4x4 drive

Switchable 4x4 drive

Wheelbase / suspension

Wheelbase 2.75 m

Seats

Comfort seat with pneumatic self-adjustment for the driver

Bench for two people with tool box

Tires

245/70 R 17.5 (143 / 141J) 17.5 x 6.75 SIMPLE

Spare wheel 245/70 R17.5 (143/141 J)

cabin

Cabin color orange RAL 2011

Heated mirrors

Outside mirror set to the outside

3-pole socket outside for winter service lighting

Winter service lighting with two headlights

Rotating beacon on pole

Socket 13 pin outside for rear attachment for trailer operation

Hydraulics

PM7-H31 2nd circuit: 14.4 cc pump movement hydraulics & 21.1 cc pump

Power hydraulics:

2x movement hydraulics, including tilting function, three-sided tipper 30l / min, max. 200 bar

Couplings 1 - 4 front right, each double-acting with floating position.

1 x single-acting for tippers with floating position. All couplings can be operated using the joystick.

1x power hydraulics P (pressure) rear right with tank return T and leakage oil line TL, 50 l / min max. 180 bar

PM7-H41 1x power hydraulics pulled to the front left with leakage oil line

(required PM7-H31) (not possible with PM7-H32)

Miscellaneous

Main battery switch compulsory in the EU

Board tool for 17.5" tires

Work lights on the rear side of the cabin

Corrosion package

Front device plate DIN B (size 3)

Trailer coupling ball head 3.5 t (type DEDALO GS501)

Construction equipment

Three-way tipper 2950x1700x400 mm compl. in aluminum for wheelbase 2.75 m

Front wall elevation for tipping bridges with aluminum or steel

Rear axle single, standard springs

Clutch booster

SSR professional footwell heating

Others

SSR-P radio / CD with MP3, USB, Bluetooth and hands-free kit