

Profile A - XHD

A 21 - XHD

Professional Aluminum Boats



S P E C S	Overall Length : 21' / 6.4m	Number of Chambers : 6	Shaft Length : 25" / 63.5cm
	Overall Beam : 9' 1" / 2.77m	Person Capacity : 17	Gas Built in Tank : 51Gal / 193 L
	Inside Length : 16' 5" / 5.0m	Weight : 1580lb / 717kg	RDC Design Category : C
	Inside Beam : 4' 6" / 1.37m	Recommended HP : 150hp / 111.9kw	
	Tube Diameter : 22" / 0.56m	Maximum HP : 200hp / 149kw	

S T A N D A R D F E A T U R E S	<ul style="list-style-type: none"> <li>■ Professional Deep "V" Marine GRADE Aluminum Hull</li> <li>■ Heavy Duty Bow Towing Post</li> <li>■ Stringer System Welded under Aluminum Deck</li> <li>■ Heavy Duty Transom Knees</li> <li>■ Integrated Marine Grade Aluminum Fuel Tank</li> <li>■ Aluminum Keel Protector</li> <li>■ Non-Skid Rubber Floor Panels</li> <li>■ Plastic External Transom Plate</li> <li>■ Aluminum Internal Transom Plate</li> <li>■ Welded Aluminum Bow Eye with SS Shackles</li> <li>■ 4 Aluminum Davit Lifting Points</li> <li>■ Aluminum Transom Tie Down &amp; Towing Rings</li> <li>■ Aluminum Bow Tie Down &amp; Towing Rings</li> <li>■ Drain Scuppers</li> <li>■ Life Line Around Tube</li> <li>■ Pressure Relief Valves</li> </ul>	<ul style="list-style-type: none"> <li>■ Non - skid (CSM) Coated Fabric on Tube's Surface</li> <li>■ Heavy Duty 1670 Decitex Orca (CSM) Five Layer Coated Fabric</li> <li>■ Double Solid Rub Rail</li> <li>■ Push Push Plastic Non-Corrosive 2 Stage Inflation Valves</li> <li>■ 1 Front &amp; 4 Side Orca (CSM) Fabric Handles on Tubes</li> <li>■ Hand Pump</li> <li>■ Maintenance Kit</li> <li>■ Owner's Manual</li> <li>■ Closed Cell Foam Upholstery</li> <li>■ Aluminum Console with Forward Seat &amp; Cushion</li> <li>■ Lean On</li> <li>■ Bow Locker/Seat</li> <li>■ Console Front Access Lid</li> <li>■ Bow Step with Fold Down Stainless Steel Cleat &amp; LED Running Lights</li> <li>■ 360° LED White Light Navigation Pole</li> <li>■ Lateral Fold Down Stainless Steel Cleat</li> </ul>	<ul style="list-style-type: none"> <li>■ Stainless Steel Console Grab Rail</li> <li>■ Plexiglass Windshield</li> <li>■ 4 Waterproof Rocker Switches with Circuit Brakers</li> <li>■ Battery Box</li> <li>■ Battery Switch</li> <li>■ Fuel and Water Separator Filter</li> <li>■ Hydraulic Steering System</li> <li>■ Stainless Steel Steering Wheel</li> <li>■ Complete Tin Wiring &amp; Heat Shrink Sealed Terminals</li> <li>■ 3 Layer Reinforced Seams</li> <li>■ Rubber Protector on Full Length of Keel</li> <li>■ Stainless Steel Gas Springs</li> <li>■ Automatic Bilge Pump</li> <li>■ Paddles With Aluminum Shaft</li> <li>■ Paddle Holders</li> </ul>
------------------------------------	--	---	---

O P T I O N A L F E A T U R E S	<ul style="list-style-type: none"> <li>■ Aluminum Light Arch</li> <li>■ Tube Chaps</li> <li>■ Boat Cover</li> <li>■ Chock Set</li> <li>■ Transom Ladder</li> <li>■ Bimini Top with Stainless Steel Tubing</li> <li>■ Console Cover</li> </ul>	<ul style="list-style-type: none"> <li>■ Lifting Harness</li> <li>■ Teak Floor</li> <li>■ CD/Radio System</li> <li>■ Compass</li> <li>■ GPS</li> <li>■ VHF Package</li> <li>■ Towing Post</li> <li>■ Engine Guard</li> </ul>
------------------------------------	---	--





S P E C S

Overall Length	: 24' 8" / 7.52m	Number of Chambers	: 6	Shaft Length	: 25" / 63.5cm
Overall Beam	: 9' 2" / 2.80m	Person Capacity	: 20	Gas Built in Tank	: 65Gal / 246 L
Inside Length	: 19' 9" / 6.02m	Weight	: 1758lb / 799kg	RDC Design Category	: C
Inside Beam	: 4' 8" / 1.42m	Recommended HP	: 150hp / 111.9kw		
Tube Diameter	: 24" / 0.61m	Maximum HP	: 250hp / 186.5kw		

S T A N D A R D  
F E A T U R E S

- Professional Deep "V" Marine GRADE Aluminum Hull
- Heavy Duty Bow Towing Post
- Stringer System Welded under Aluminum Deck
- Heavy Duty Transom Knees
- Integrated Marine Grade Aluminum Fuel Tank
- Aluminum Keel Protector
- Non-Skid Rubber Floor Panels
- Plastic External Transom Plate
- Aluminum Internal Transom Plate
- Welded Aluminum Bow Eye with SS Shackles
- 4 Aluminum Davit Lifting Points
- Aluminum Transom Tie Down & Towing Rings
- Aluminum Bow Tie Down & Towing Rings
- Drain Scuppers
- Life Line Around Tube
- Pressure Relief Valves
- Non - skid (CSM) Coated Fabric on Tube's Surface
- Heavy Duty 1670 Decitex Orca (CSM) Five Layer Coated Fabric
- Double Solid Rub Rail
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- 1 Front & 4 Side Orca (CSM) Fabric Handles on Tubes
- Hand Pump
- Maintenance Kit
- Owner's Manual
- Closed Cell Foam Upholstery
- Aluminum Console with Forward Seat & Cushion
- Lean On
- Bow Locker/Seat
- Console Front Access Lid
- Bow Step with Fold Down Stainless Steel Cleat & LED Running Lights
- 360° LED White Light Navigation Pole
- Lateral Fold Down Stainless Steel Cleat
- Stainless Steel Console Grab Rail
- Plexiglass Windshield
- 4 Waterproof Rocker Switches with Circuit Brakers
- Battery Box
- Battery Switch
- Fuel and Water Separator Filter
- Hydraulic Steering System
- Stainless Steel Steering Wheel
- Complete Tin Wiring & Heat Shrink Sealed Terminals
- 3 Layer Reinforced Seams
- Rubber Protector on Full Length of Keel
- Stainless Steel Gas Springs
- Automatic Bilge Pump
- Paddles With Aluminum Shaft
- Paddle Holders

O P T I O N A L  
F E A T U R E S

- Aluminum Light Arch
- Tube Chaps
- Boat Cover
- Chock Set
- Transom Ladder
- Bimini Top with Stainless Steel Tubing
- Console Cover
- Lifting Harness
- Teak Floor
- CD/Radio System
- Compass
- GPS
- VHF Package
- Towing Post
- Engine Guard

