

SPECIFICATIONS

SPECIFICATIONS	Kayo126 DS		T1800 DS	T2600 DS	T3200 DS
PRINTHEAD COUNT	8*	12	2 or 4**	2 or 4**	2 or 4**
PRINTHEAD TECHNOLOGY	Ricoh Gen-4	Ricoh Gen-4	Kyocera	Kyocera	Kyocera
PRODUCTION SPEED – SQ FT	560	870	1340	1570	1690
PRODUCTION SPEED – SQ M	52	81	130	146	157
WEIGHT	3306 lbs (1500 kg)		2314 lbs (1050 kg)	2755 lbs (1250 kg)	3196 lbs (1450 kg)
WIDTH – IN	126		74	102	126
WIDTH – M	3.2		1.9	2.6	3.2
DIMENSIONS – IN (W x D x H)	209 x 47 x 63		156 x 47 x 63	180 x 47 x 63	209 x 47 x 63
DIMENSIONS – CM (W x D x H)	530 x 120 x 160		395 x 120 x 180	460 x 120 x 180	530 x 120 x 180
ELECTRICAL REQUIREMENTS	VAC 50/60 Hz, Single-phase, 208-220V 32A		3-phase 400V Wye connection with neutral wire 32A 50/60 Hz		
AMBIENT TEMPERATURE	68°F – 77°F (20°C – 25°C)				
RELATIVE HUMIDITY	40% – 80% (non-condensing)				
MEDIA HANDLED	Roll				
INKS					
Colors	4 Colors: CMYK				
Type	Water-Based Dye Sublimation				
Capacity	2.5-Liter Bulk Ink Feed				
RESOLUTION	1200 dpi				

*Field upgrade from 8 to 12 printheads available

** Field upgrade from 2 to 4 printheads available