



Gfp **Graphic Finishing**
partners

Where Finishing Comes First.

Gfp 563TH-4R MaxPro

ProductionTop Heat Laminator

What's the best way to make your production even better? Shorten film loading time? Make fewer film changes? Increase throughput speed? The 563TH-4R does all that and more.

MAXIMUM PRODUCTIVITY

50% faster throughput

FAST ROLL CHANGES

Front/Rear Swing-out shafts

EASY LOADING

3" Aluminum Quick-Grip shifts

RUGGED DESIGN

Metal Alloy heaters

VERSATILE

Roll-to-Roll operation



overlamination • mounting • board pre-coating

Spend less time on set-ups and changeovers with swing-out supply shafts.

50% faster throughput and quick application changes save time, effort and money.



- Swing-out Quick-Grip supply shafts
- Drop-in Quick-Grip rewind shafts
- Photoelectric eye for safety
- Motorized rear rewind **INCLUDED**
- Optional rear rewind with slit
- Swing-up feed table & 38" output height
- Metal Alloy heater reduces breakage
- 4.4" diameter rollers
- Roller gap measurement scale



Includes motorized rear rewind for roll-to-roll applications (563TH-4R)



Optional Rear Rewind with Slitter (563TH-4RS)



Media Alignment disks keep supply rolls from telescoping

563TH-4R

Rugged Design
Professional Quality
Proven Performance
Economically Priced

APPLICATIONS

Signs
Banners
POP Displays
Trade show displays
Graphic mounting
Photo mounting
Dry-erase boards
Floor graphics
Window graphics
Vehicle graphics

Warranty:

1 year parts & labor.
Installation is available.

<i>Laminating Width</i>	63"
<i>Roller Diameter</i>	4.4"
<i>Roller Gap</i>	1"
<i>Rear rewind</i>	Included 563TH-4R
<i>Rear rewind with Slitter</i>	Optional 563TH-4RS
<i>Maximum temperature</i>	140°F
<i>Laminating speed</i>	0-20 ft/min
<i>Pressure adjustment</i>	Hand Wheel
<i>Heat method</i>	Metal Alloy heater
<i>Max. roll diameter</i>	8" OD (top); 16" OD (bottom)
<i>Supply Shafts</i>	2 Swing-out
<i>Tension Adjustment</i>	Single knob
<i>Power Supply</i>	110v 12A
<i>Power Consumption</i>	1320W
<i>Foot Pedal</i>	Included
<i>Stand with casters</i>	Included
<i>Net Weight w/ stand</i>	491 lbs.
<i>Dimensions</i>	87" x 26.5" x 52.5"
<i>Machine Shipping</i>	711 lbs. 89" x 35.5" x 31.5"

cTUVus
 Safety
 Approval



Your local dealer is:

