

The PerformanceJet 2508UF

Smart Printing Equals Value




4' x 8' Flatbed UV-LED Printer

The Mutoh PerformanceJet 2508UF 4'x8' UV-LED Flatbed printer excels in performance, quality and value. It's standard, staggered four printhead design - field upgradeable to six heads when adding white and varnish ink, provides high print speeds and the dual UV lamps on both sides of the carriage provide exceptional cure times allowing for higher production capacity. Print media up to 4" thick and use the CMYK x2 or CMYK x2 plus white & varnish to create stunning applications with outstanding durability and color gamut. The PJ 2508UF comes standard with an automatic media registration pin system with "blow back" feature for easier handling and positioning of media, an anti-static system and an automatic media thickness detector. The PerformanceJet 2508UF delivers outstanding output you expect and provides the reliability you need in a UV-LED flatbed making it the smart choice for any production shop.



ANATOMY OF A PERFORMANCEJET 2508UF



Print method	Drop-On Demand, Piezo Drive Method
Variable dot	Yes
# of nozzles	1280 (4X320 Channels / 4 heads -default)
# of print heads	4 default - field upgradeable to 6 (when adding white and varnish ink)
Ink type	UV-LED
Curing system	UV-LED Lamp
Maximum print Area	100" X 49.2"
Print modes	600X300 / 600X600 / 600X900 / 600X1200 (dpi) *
Color options	CMYK x2 or CMYK x2, +White + Varnish
Maximum print speed / resolution	968 sqft/hr (600X300 / 2 pass / 4 color / 4 head)
Maximum Resolution	600 x 1200 dpi
Maximum Print Height	4 inches (101.6mm)
Maximum media weight	92.15 lbs. / sq yd. or 350lbs.

Media Handling System	4 Zone Vacuum Table Auto Media Registration Pin System
Media Handling System 2	"Blow Back" Feature to easily slide media across table.
Auto Media Thickness Detection	Included
Anti Static Elimination	Included
RIP software	Mutoh Edition Flexi Sign & Print
Power requirements	Main: 220 - 240 VAC, 50/60Hz +/-1 Hz 25A Single Phase
Operating temperature	68°F - 86°F
Operating humidity range	40% - 80% (non condensing)
Dimensions (printer) WxDxH	186.6" x 78.7" x 58.8"
Dimensions (Shipped) WxDxH	196.9" x 89" x 66.1
Printer weight	2,756 lbs (1,250 kg)
Shipped weight	3,616 lbs (1,640 kg)
Limited warranty	1 Year Onsite

*Actual print mode specifications are 605 X 300 / 605 X 600 / 605 X 900 / 605 X 1200 dpi



Custom Backslashes



Packaging



Industrial



Room Dividers

- ✓ UV-LED is an environmentally friendly ink type.
- ✓ Easily create large signs, custom packaging and print industrial applications and much more.
- ✓ Use the blow back feature to easily handle heavier media across the table.
- ✓ Print up to 4" (101.6mm) thick, perfect for doors, room dividers, back slashes and other large items.
- ✓ Scale your ink configuration with your business. Field upgradeable from CMYKx2 to CMYKx2 +W+V.

Free Print Sample

www.mutoh.com
1-800-99MUTOH

Easy Financing options with

MUTOH
FINANCIAL SERVICES