

Media



0 11	
Sealing Area	
Maximum Product Size (W x L x H)	22.00" x 16.00" x 9.00"
Center Folded Film Types	Polyolefin / PVC
Maximum Roll Width	24.00"
Maximum Roll Diameter	10.00"
Adjustable Product Height	✓
Programmable Seal Arm Opener	✓
Teflon Coated Sealing Blade	✓
Programmable Sealing Blade Temperature	✓
Performance	
Wraps per Minute*	up to 16 items
1 Power Source	✓
External Pneumatic Seal Pressure Required	No
Heater Tunnel Wattage	5700W
Power Supply	208V / 3ph / 20A
Display & Controls	
Water Resistant LED Display	✓
Digital Controls	✓
Customizable Programs	6
Operational Features	
Machine Type	Semi-Automatic
Automatic: Seal»Cut»Release»Advance	✓ ✓
Sealing Blade Heat	Impulse
3 Working Modes	Bag Only / Bag & Shrink / Multiples
Precision Blade Cooling System	Coolant Fluid
Sealing Activation Modes	Timer / Push Button / Foot Pedal (optional)
Automatic Seal Arm Closure	✓
Automatic Cool-Down	√
Auto-Discharge Conveyer	✓
Conveyor Belt Modes	Continuous / Step- Advance
Programmable Conveyer Speed	✓
Automatic Waste Winder	✓
Tearless Perforation System	✓
Double-Insulated Tunnel Walls	✓
18" Exit Roll Conveyor	✓
Overheat Safety Circuit	✓
Patented Safety System	✓
Service	
Easy Frontal Access	
Indicating Display	· ·
Error Codes	· ·
1 Year Limited Warranty	√
Housing & Dimensions	
	Ota al / Dalva d E
Material Width v. Longth	Steel / Baked Ename 91.00" x 28.50"
Width x Length	
Height (Lid open/closed)	54.50" / 34.50"
Working Height	32.00"
Locking Casters	√ 755lbc
Shipping Weight	755lbs
Optional Features	01
Stainless Entry Plate	Standard
Single Hole Punch	115V
Foot Pedal	√
Entry Film Opener	√
Teflon Belt for Tunnel	√
Shrink System	

^{*}Depends on type of product, film and operator ability. Specifications may change without notice.