

Graphic Lamination Products

RSC Series

RSC-1650C / 1650H

- Best-in-class dual roll 65" (1650mm) cold laminator
- Ideal multi-function laminator for sign shops
- Heavy duty silicone rubber rollers - 3.75" (95mm diameter)
- Mounting up to 0.6" (15mm)
- Remote control (foot pedal and mouse)
- 9 speed settings up to 16.5 ft/min (5m/min)
- Chain-drive synchronized take-up device
- Cross cutter
- Heat-assist top roller on RSC-1650H (up to 122°F / 50°C)



RSC-1400C

- Laminates up to 55" (1400mm)
- High quality silicone rubber rollers
- Mounting up to 0.6" (15mm)
- Remote control (foot pedal and mouse)
- 9 speed settings up to 16.5 ft/min (5 m/min)
- Chain-drive synchronized take-up device
- Auto-grip hubs for easy replacement of film rolls

■ Application

Outdoor signage; Vehicle wraps; Fleet graphics; Heat-sensitive digital graphics; Premask; Mounting

■ Specifications

Films are available in both industry standard and custom size rolls

Description	RSC-1400C	RSC-1650C	RSC-1650H
Power Supply	120V 60Hz	120V 60Hz	120V 60Hz
Power Consumption	100W	100W	1200W
Max. Laminating Width	55" / 1400mm	65" / 1650mm	65" / 1650mm
Film Thickness	1-10mil / 25-250mic	1-10mil / 25-250mic	1-10mil / 25-250mic
Max. Laminating Speed	16.4 ft/min / 5 m/min	16.4 ft/min / 5 m/min	16.4 ft/min / 5 m/min
Ready Time	Not applicable	Not applicable	10 min
Heating Method	None	None	Upper Heat Assist Roller
Driving Motor	DC geared	DC geared	DC geared
Max. Temperature Control	Not applicable	Not applicable	122°F / 50°C
Speed Control	9 Settings	9 Settings	9 Settings
Transport Type	2 Roller	2 Roller	2 Roller
Film Core Size	Auto grip 3"	Auto grip 3"	Auto grip 3"
Side Cutter	No	No	No
Cross Cutter	Yes	Yes	Yes
Film Alignment	No	No	No
Hot Lamination	No	No	No
Cold Lamination	Yes	Yes	Yes
Mounting Thickness	0.6" / 15mm	0.6" / 15mm	0.6" / 15mm
Take Up System	Chain link to main motor	Chain link to main motor	Chain link to main motor
Paper Counter	No	No	No
Length Measurement	No	No	No
Reverse	Yes	Yes	Yes
Remote Control	Yes	Yes	Yes
Foot Pedal	Yes	Yes	Yes
Unit Dimensions (WxDxH)	67.5" x 25.5" x 47.5" 1710 x 650 x 1210 mm	77" x 25.5" x 47.5" 1960 x 650 x 1210 mm	77" x 25.5" x 47.5" 1960 x 650 x 1210 mm
Unit Weight	361 lbs / 164 kg	461 lbs / 209 kg	399 lbs / 181 kg
Carton Dimensions (WxDxH)	77" x 35.5" x 33.5" 1960 x 900 x 850 mm	86" x 35.5" x 57.5" 2190 x 900 x 1460 mm	86" x 35.5" x 57.5" 2190 x 900 x 1460 mm
Carton Weight	595 lbs / 271 kg	745 lbs / 338 kg	684 lbs / 310 kg