

Image® 600 Laminators

A cost-effective way to capitalize on profitable, large-format display opportunities, the Image 600 offers you full-featured finishing capabilities up to 61" (155 cm) wide.

The Image 600 is capable of cold or heat-activated overlaminating and hot sealing. Ideal for finishing ink jet, photographic and electrostatic prints.

Image® 600-S Laminators

The Image 600-S features a heated top roller and offers complete pressure-sensitive mounting and laminating and two-pass hot sealing up to 61" (155 cm) wide, making it perfect for wide-format ink jet prints.

Primary Applications

The Image 600 and 600-S offer pressure-sensitive mounting and heat-activated mounting and laminating; heat-assisted, and heat-activated mounting and laminating; and hot sealing in one pass with the 600 model and 2 passes with the 600-S.



Features

- High-release silicone rollers for easy cleaning
- Pneumatic pressure adjustment with fine-tune control for a smooth finish
- Electric heat with digital controls for even heating and maximum accuracy
- Dial-in roller height adjustment for fast, accurate nip setting
- Vacuum feed table for flat, wrinkle-free feeding of digital prints
- Cooling fans for smooth output when encapsulating
- Swing-out supply shafts with brakes for easy loading and precise film tension adjustment
- Digital media roll easel for convenient roll-to-roll laminating
- Automatic upper take-up shaft for removing release lines
- Easy-to-use controls & foot pedal for hands-free operation
- Comprehensive safety systems with emergency stops and electric eyes
- Floor cart with wheels

Image® 600 Laminators

SPECIFICATIONS

Specifications	Image® 600	Image® 600-S
Maximum Working Width	61" (155 cm)	61" (155 cm)
Maximum Working Width (heated encapsulation)	55" (140 cm)	55" (140 cm)
Maximum Speed	10 fpm (3.1 mpm)	10 fpm (3.1 mpm)
Maximum Roll Opening	1 1/8" (29 mm)	1 1/8" (29 mm)
Maximum Roll Temperature	250°F (121°C)	250°F (121°C)
Dimensions	78" w x 32" d x 50" h 198 cm x 81 cm x 127 cm	78" w x 32" d x 50" h 198 cm x 81 cm x 125 cm
Net Weight	550 lbs. (251 kg)	550 lbs. (251 kg)
Shipping Weight	850 lbs. (389 kg)	850 lbs. (389 kg)
Mechanical Requirements	2 CFM compressed air @ 100 psi, 0.25" (0.6 cm) ID flex. line	2 CFM compressed air @ 100 psi, 0.25" (0.6 cm) ID flex. line
Electrical Requirements*	208-240 VAC 50/60 Hz, single phase, 30 Amp or 380-415 VAC 50/60 Hz, three phase, 15 Amp	208-240 VAC 50/60 Hz, single phase, 15 Amp
Maximum Power Consumption	7,200 Watts	3,600 Watts

* Important: SEAL® recommends that your laminator be installed by a licensed electrician in accordance with electrical codes in your area. Specifications subject to change without notice.

Image® and SEAL® are registered Brands of Hunt Corporation



Hunt Corporation
One Commerce Square
2005 Market Street
Philadelphia, PA
19103-7085
Tel: 215-656-0300
Fax: 215-656-3700
www.hunt-corp.com

Hunt Corporation
P.O. Box 5819
2020 W. Front St.
Statesville, N.C. 28677
Tel: 1-800-873-4868
Fax: 1-704-873-1766

Hunt Graphics
Europe Limited
1 Watkins Close
Burnt Mills Industrial Estate
Basildon, Essex SS13 1BJ
United Kingdom
Tel: 44 1268 530 331
Fax: 44 1268 729 442

Hunt Graphics
Europe BV
Kanaalstraat 0.Z. 3
P.O. Box 29,
8100 AA Raalte
The Netherlands
Tel: 31 572 345 500
Fax: 31 572 345 501

Hunt Graphics
Pacific Limited
Unit A, 13th Floor, Block 1
Leader Industrial Centre
Tsuen Wan,
New Territories,
Hong Kong
Tel: 852 2407 3738
Fax: 852 2408 0973

Hunt Corporation
Canada
690 Gars Court
Mississauga, Ontario
Canada, L5S 1P2
Tel: 905 564 7717
Fax: 905 564 7079

Contact your local distributor:

