

1.0 Shipping Dimensions (includes Pallet and wooden crate)

	Main Unit (Printer)	Feeding Table (each)
Weight (lbs)	11,000	2600
Length (inches)	236	138
Width (inches)	88	65
Height (inches)	88	66

2.0 Requirements for Installation

2.1 Access to Facility / Final Location

Minimum door opening

Height 85 inches *

Width 79 inches

* Door must accommodate the machine height (77") plus transport rollers (provided by the riggers).

Note: The uncrated, unassembled machine is 77" x 230", this needs to be taken into account when the riggers are planning the transportation to its final location.

2.2 Rho 900 Room

Footprint (including automated load and standard output table, light trap and ink loading door) not including access or work space

24 wide x 22 long (feet)

Floor loading capacity

15,000 lbs/sq ft

3.0 Unloading from truck

3.1 Fork truck capacity (consult rigging company based on 11,000 lb weight of packed machine)

15,500 lbs

3.2 Fork minimum fork length

71 inches

3.3 Fork minimum spread

60 inches

3.4 Fork maximum width

10 inches

Important Notes:

Durst US is not responsible for the fork truck, unloading, movement or placement of the machine and recommends consulting and the use of Riggers.

Do not use any type of crane for unloading.

Warehouse storage prior to install can not be below 40 degrees F