

A Professional Finish Without A Lot Of Fuss

Compact and easy to use, the SEAL® 44 Ultra is an ideal first laminator for businesses introducing image finishing. It's also a good complementary machine for those wanting to add to existing laminating services. It can handle a broad range of applications and materials up to 42 inches (1,065mm) wide, allowing you to quickly and professionally finish rigid and flexible indoor displays and floor graphics, as well as backlit and pop-up displays.

High-Quality Performance From A Full-Featured Laminator

The professional features of the SEAL 44 Ultra assure easy operation and high-quality output for every project. You can control the temperature settings and film tensions for use with a range of films and adhesives, for an even, smooth finish. Auto-grip shafts make quick work of loading your materials and the silicone-coated rollers make the whole process simple and easy to clean up afterwards.

All This And A Name You Can Trust

To assure the highest level of results for your projects, we recommend you use the SEAL 44 Ultra with the extensive range of laminating films and adhesives from SEAL Brands. And for the ultimate in simplicity, try ProSeal™ pouch boards and pouches.



Features

- Touch pad control panel for easy use, with lighted indicators to show progress
- Single control knob to adjust for thicknesses up to 1/2" (12.7 mm)
- Adjustable speed dial lets you control settings
- Auto-grip shafts for easy loading of materials
- Silicone-coated rollers for easy cleaning
- Three temperature settings for use with a wide range of films and adhesives: 125°F (50°C); 195°F (90°C); 250°F (120°C)
- Internal heating element assures even temperature across the length of the rollers
- Material shaft brake lets you adjust film tension for a flat and even finish
- Foot control for hands-free operation
- Comprehensive safety system with emergency stops



1. Single control knob to adjust for substrate thicknesses.
2. Simple control panel showing temperature and speed adjustments.



Auto-grip shafts for easy loading and positioning of materials plus integral brake for simple film tension adjustment.



Innovative method for removing release liners.

SEAL® 44 Ultra Laminator

SPECIFICATIONS

Specifications	SEAL 44 Ultra
Max. Working Width	44" (1117 mm)
Max. Speed	4.8 ft/min. (1.5 m/min.)
Max. Substrate Thickness	1/2" (12.7 mm)
Max. Roller temperature	250°F (120°C)
Dimensions	Width: 58" (1480 mm) Depth: 22" (570 mm) Height: 43" (1105 mm)
Net Weight	242 lbs. (110 kg)
Shipping Dimensions	Width: 67" (1700 mm) Depth: 27" (700 mm) Height: 27" (700 mm)
Shipping Weight	331 lbs. (150 kg)
Electrical Requirements	Single Phase 115 VAC, 50/60 Hz, 9A 110 VAC, 50/60 Hz, 16A
Safety Certification	cETL, CE
Warranty	1 year parts (excluding rollers-180 days), 180 days labor

Neschen Americas
7091 Troy Hill Drive
Elkridge, MD 21075
Tel: 410-540-8900
Fax: 410-579-8960

Neschen Americas Canada
1601 Matheson Blvd. E.
Mississauga, Ontario
Canada, L4W 1H9
Tel: 905-212-9232
Fax: 905-212-9313

CE cETL



www.neschenamericas.com

Contact your local distributor:

Neschen Americas recommends HP Designjet Printing Systems