

GenSet



MG 50 SS-Y STAGE IIIA



GEN SET S.p.a.

Via Stazione,5 - 27030 Villanova D'Ardenghi (Pavia) Italy

Tel. (+39) 0382-5091 - Fax (+39) 0382-509-244

E-mail: commerciale@genset.it - internet: [//www.genset.it](http://www.genset.it)

**SUPER SILENCED POWER GENERATOR
 OUTPUT POWER 42,5 KVA THREE-PHASE AND 14,2 KVA SINGLE-PHASE
 DIESEL ENGINE 1500 RPM**

Standard Features	<ul style="list-style-type: none"> + Controller with digital display for full monitoring of generator parameters: 3-phase generator voltage, 3-phase mains voltage, battery voltage, ammeter, frequency, hour meter, oil pressure, engine temperature, fuel level, fail to start; with auto engine protection shutdown system in case of: <ul style="list-style-type: none"> - fail to start - emergency stop - low oil pressure - low fuel level - high coolant temperature - oil pressure sender open circuit - over/under voltage - over/under frequency - open door + Foreseen for AMF-ATS or Remote control operation + Separate tank facility c/w quick release coupling 	<ul style="list-style-type: none"> + 12 V built-in battery + 1 x 400V three-phase output + 1 x 400V - 32A EEC three-phase socket + 1 x 400V - 63A EEC three-phase socket + 4 x 230V - 32A EEC single-phase sockets + 2 x 230V - 16A EEC single-phase sockets + Power output protection + Earth leakage relay + Emergency stop button + Automatic voltage regulator + Engine oil drain manual pump + Central lifting eye + Fork-lift pockets + Bunded base to retain all liquids
Options available as factory options	<ul style="list-style-type: none"> + Versions with different voltages + 60Hz version + Spark arrester muffler + Engine heater + Long run fuel tank (24h) complete with bunded base 	
Accessories on request	<ul style="list-style-type: none"> + GRT2W: two-wheels site tow undercarriage + Auto Transfer Switch (ATS) panel complete with battery charger for auto-start operation + Remote Start/Stop kit by cable (20/50 m) 	
Noise level	+ Lwa 92 (67 dB at 7 m)	
AC generator - 50Hz	<ul style="list-style-type: none"> + Type: synchronous + Three-phase power (stand-by): 42,5kVA - 400V + Three-phase power (prime): 40kVA - 400V + Single-phase power (max.): 14,2kVA - 230V + Power factor: $\cos \phi$ 0,8 	
Diesel Engine 1500 rpm	<ul style="list-style-type: none"> + Type: Yanmar 4TNV98T - STAGE IIIA - 4 cyl. - 3319 cm³ + Max power: 55,9 HP (41,7 kWm) + Starting system: electric (12Vdc) + Cooling system: water + Fuel consumption @ 75%: 8,1 l/h 	
Other features	<ul style="list-style-type: none"> + Insulation Class: H + Ambient temperature: 40 °C (*) + Altitude: 1000 m (*) + Mechanical Protection: IP 23 + Fuel tank capacity: 115 l + Dimensions (L x W x H): 1974 x 913 x 1420 mm + Dry weight: 945 kg 	

(*) - For altitude and temperature values higher than those listed above, please consult the manufacturer to verify the available power.

In line with our continued development, innovation and voice of customer program, we reserve the right to change data without notice.