

OLIN ENGINEERING, INC

15622 COMPUTER LN HUNTINGTON BEACH, CA 92649 PH 714 897 1230 F 714 892 9268

WWW.OLINPUMP.COM

DAVE@OLINPUMP.COM



SPECIFICATIONS 5 75/100 1/2" MINUS FOUNDATION PUMP



LEG-MOUNTED MODEL SHOWN

	5 75CA	5 100CA
OUTPUT: cmh /cyh	61/80	84/110
DELIVERY PRESSURE: bar/psi		63/900
DELIVERY CYLINDER: mm/inch		203/8
STROKE: mm/inch	610/24	914/36
STROKES/MINUTE:	54	47
ENGINE POWER: kw/hp	75/100	98/130
HOPPER CAPACITY: l/gal		340/90
OUTLET: mm/inch		100/4
OIL COOLER		YES
CONTROL SYSTEM:	ELECTRIC/HYDRAULIC	
HYDRAULIC CAPACITY: l/gal		338/89
WEIGHT: kg/lbs	2585/5700	2780/6130
LENGTH: cm/inch		445/175
WIDTH:		178/70
HEIGHT:		208/80

The 5 75 & 100's 8" delivery cylinders combined with the Millennium Series manifold, handle high sack structural 1/2" minus & grout mixes, making them the perfect choice for Auger Cast Pile and large slurry backfill jobs.

*All OLIN Ball Valve pumps feature delivery system pressure release valve standard.



**GROUT – SHOTCRETE – CONCRETE – PRESSURE GROUTING
AND SPECIAL APPLICATION PUMPS**