MODEL 901 - 3600



Calender used for:

- Transfer printing
- Direct inks reactivation
- Thermosetting heatsetting

1. Characteristics of printing cylinder:

1.1. Diameter: 350 mm (13,78"). 1.2. Width: 3.600 mm (141,73").

1.3. Working width: 3.400 mm (133,86").

2. Heating system and temperature control:

- 2.1 The cylinder is heated by 2 resistors (heating element) in a vacuum sealed oil bath, in complete absence of air and pressure. MONTI ANTONIO S.p.a system.
- 2.2 The temperature of the cylinder is set by touch screen and regulated by an electronic thermostat and equipped with temperature alarm system and a limitation system of maximum temperature (230 °C).

3. Tension controls:

- 3.1. Tension control for printing material
 - Entry: disk brake with pneumatic adjustment and fabric manual brake
 - Exit: independent motor, adjustable by potentiometer
- 3.2. Tension control for printing paper
 - Entry: disk brake with pneumatic adjustment.
 - Exit: independent motor, adjustable by potentiometer
- 3.3. Tension control for protection paper
 - Entry: disk brake with pneumatic adjustment.
 - Exit: independent motor, adjustable by potentiometer

4. Other devices into machine:

- 4.1. Independent motors with a electronic synchronization system
- 4.2. NOMEX felt with tension adjustment system and automatic felt-centering device
- 4.3. Incorporated system of felt protection in case of black out and/or compressed air lack
- 4.4. Front touch-screen keyboard for production data access and programming

5. <u>Technical data:</u>

5.1. Installed power: 42 kw

5.2. Average electrical consumption: 30 kw/h

5.3. Compressed air pressure: 6-8 bar

All data and technical features are purely indicative and subjected to changes without prior notice **MONTI ANTONIO**

INNOVATION SPEED FLEXIBILITY PROJECT&DESIGN INSTALLATION AND ASSISTANCE STANDARD & CUSTOM HEATING SOLUTIONS

MODEL 901 - 3600



- 5.4. Mechanic speed: 0.3 4 m/min
- 5.5. Overall dimensions: width 5.050 mm (198,82"). length 1.950 mm (76,77"). height 2.100 mm (82,68").
- 5.6. Net weight: 4.500 kg
- 5.7. Machine produced according to CE rules
- 5.8. Customs tariff: 84 51 80 30