

VOITH

VOITH, INC.

2620 E. Glendale Avenue, Appleton, Wisconsin 54915, Telephone (414) 731-7724, Telex 260364, Telefax (414) 731-0240

PULPER

RIGHT ANGLE REDUCER

Certification Sheet

IDENTIFICATION	CUSTOMER <u>S. D. WARREN</u>	CUST. DESIGNATION <u>DRY FIBER PULPER</u>
	ADDRESS(ORDER) <u>MUSKEGON, MI</u>	
	ADDRESS(INSTALL) <u>SAME</u>	TYPE/SERIAL NO.(S) <u>*54/43HOAGV-273</u>
	CUST. ORDER NO. <u>G76370092</u>	VOITH JOB NO. <u>589-5552</u> <u>GV15-94</u>
	CUST. EQUIP. NO. _____	ORDER DATE <u>2-14-89</u>
	CONTROLS BY <u>CUSTOMER</u>	CONTROLS SERIAL NO. <u>*</u>
	CERTIFIED BY <u>John Fischer</u>	TITLE <u>PRODUCT ENGINEERING</u>
JOHN FISCHER		
APPLICATION	INSTALLATION DWG. <u>D21-130126</u>	STOCK _____
	STOCK CONSISTENCY <u>4.5%</u> <u>AD/BD</u> pH _____	TEMP _____
	TANK BY <u>VOITH</u> DIM: <u>210.0</u> ID _____	HEIGHT <u>212.0</u> MAT'L <u>316L SS</u>
	CAP. AT OPER. LEVEL <u>2000</u> CU.FT.	IMPELLER RPM <u>201</u>
	EXTRACTION HOLE SIZE <u>.750</u>	BLADE TYPE <u>H206 RH</u>
	DEFIBERING RING <u>-----</u>	EXTRACTION: <u>WITHXXXXXXHXXX</u>
MAT'L	PULPING UNIT <u>316 SS</u> EXTRACTION PLATES <u>316 SS</u> EXTRACTION CHAMBER <u>316 SS</u>	
	DEFIBERING RINGS <u>----</u>	
DRIVE	REDUCER BY <u>VOITH</u> MODEL <u>GV-15-94 X</u> RATIO <u>5.87:1</u>	
	LO-SPEED _____ HI-SPEED _____	MECH. HP RATING <u>1077</u>
	COUPLING BY <u>VOITH</u> MFG <u>DODGE</u> TYPE <u>PARA-FLEX</u>	SIZE <u>PX200</u>
	MOTOR BORE <u>3.625</u> KW <u>.875x.437</u>	RED. BORE <u>4.00</u> KW <u>1.0 x .50</u>
MOTOR	MOTOR BY <u>CUST</u> HP <u>400</u> RPM <u>1200</u> FRAME SIZE <u>588U</u>	
		<u>M-5244</u>
OPTIONAL ITEMS	BY VOITH ONLY IF MARKED	
	☐ CONTROL PANEL	☒ COUPLING GUARDS ☐ STEAM VALVES
	☐ " DUMP VALVE	☒ 16 " JUNK TRAP ☐ TANK MANWAY
REMARKS	* ALWAYS SPECIFY UNIT SERIAL NO. WHEN ORDERING SPARE PARTS	
	REV.1 5/17/89	
	CORRECTED MOTOR FRAME SIZE	

8057627

8057634

8065131

8065288

8065290

8065289

8064390