

FARO® Laser Scanner Focus^{3D} X 330

The Perfect Instrument for 3D Documentation and Land Surveying

FARO



EXTENDED SCANNING - 330M RANGE

The Focus^{3D} X 330 can scan objects up to 330 meters away. Large buildings, land-site excavations and vast terrains can be surveyed with fewer scans, thus resulting in quicker project scanning completion.

EASY POSITIONING - INTEGRATED GPS RECEIVER

With its integrated GPS receiver, the laser scanner is able to correlate individual scans in post-processing making it ideal for surveying based applications.

OUTDOOR SCANNING CAPABILITY

The Focus^{3D} X 330 is able to perform fast and highly precise scanning in direct sunlight.

LOW NOISE PERFORMANCE

The FARO Focus^{3D} X 330 delivers extraordinary scan data quality at extended range with very low noise.

WIRELESS LAN

WLAN remote control permits you to start, stop, and view scans at a distance.

EXTENDED OUTDOOR SCANNING IN FULL SUNLIGHT

The FARO Focus^{3D} X 330 is a high-speed 3D scanner with extra-long range. The Focus^{3D} X advances into entirely new dimensions: it can scan objects up to 330 meters away even in direct sunlight.

With its integrated GPS receiver, the laser scanner is able to correlate individual scans in post-processing making it ideal for surveying based applications.

With its increased range and scan quality, the FARO Focus^{3D} X 330 considerably reduces the effort involved in measuring and post-processing. The 3D scan data can easily be imported into all commonly used software solutions for accident reconstruction, architecture, civil engineering, construction, forensics, industrial manufacturing and land surveying. Distance dimensions, area and volume calculations, analysis and inspection tasks and documentation can thus be carried out quickly, precisely and reliably.

BENEFITS

The FARO Focus^{3D} X 330 is the leading tool for surveying and 3D documentation.

Scanning range - 330m, integrated GPS, the possibility to work in direct sunlight as well as the specially for the scanner designed protection cover make it a ideal tool for outdoor environments.

FARO® Laser Scanner Focus^{3D} X 330

www.faro.com

PERFORMANCE SPECIFICATIONS FOCUS^{3D} X 330

Ranging unit

Unambiguity interval: By 122 till 488 Kpts/sec at 614m; by 976 Kpts/sec at 307m
Range Focus^{3D} X 330: 0.6m - 330m indoor or outdoor with upright incidence to a 90% reflective surface
Measurement speed (pts/sec): 122,000 / 244,000 / 488,000 / 976,000
Ranging error¹: ±2mm

Ranging noise ²	@10m	@10m - noise compressed ³	@25m	@25m - noise compressed ³
@ 90% refl.	0.3mm	0.15mm	0.3mm	0.15mm
@ 10% refl.	0.4mm	0.2mm	0.5mm	0.25mm

Colour unit

Resolution: Up to 70 megapixel colour
Dynamic colour feature: Automatic adaption of brightness
Parallax: Co-axial design

Deflection unit

Field of view (vertical/horizontal): 300°⁵ / 360°
Step size (vertical/horizontal): 0.009° (40,960 3D-Pixel on 360°) / 0.009° (40,960 3D-Pixel on 360°)
Max. vertical scan speed: 5.820rpm or 97Hz

Laser (optical transmitter)

Laser class: Laser class 1
Wavelength: 1550nm
Beam divergence: Typical 0.19mrad (0,011°) (1/e, halfangle)
Beam diameter at exit: Typical 2.25mm (1/e)

Data handling and control

Data storage: SD, SDHC™, SDXC™; 32GB card included
Scanner control: Via touchscreen display and WLAN
New WLAN access: Remote control, scan visualisation are possible on mobile devices with Flash®

Multi-Sensor

Dual axis compensator: Levels each scan: Accuracy 0.015°; Range ± 5°
Height sensor: Via an electronic barometer the height relative to a fixed point can be detected and added to a scan.
Compass⁴: The electronic compass gives the scan an orientation. A calibration feature is included.
GPS: Integrated GPS receiver

**CLASS 1
LASER PRODUCT**

¹ Ranging error is defined as a systematic measurement error at around 10m and 25m, one sigma. Improved compensation available for dedicated mounting (fee-based service). ² Ranging noise is defined as a standard deviation of values about the best-fit plane for measurement speed of 122,000 points/sec.³ A noise-compression algorithm may be activated thereby compressing raw data noise by a factor of 2 or 4. ⁴ Ferromagnetic objects can disturb the earth magnetic field and lead to inaccurate measurements. ⁵ 2x150° Homogenous point spacing is not guaranteed. Subject to change without prior notice.

GENERAL

Power supply voltage: 19V (external supply)
14.4V (internal battery)
Power consumption: 40W and 80W
(while battery charges)
Battery life: 4.5 hours
Ambient temperature: 5° - 40°C
Humidity: Non-condensing

Cable connector: Located in scanner mount
Weight: 5.2kg
Size: 240 x 200 x 100mm
Maintenance / calibration: Annual



GSA Contract Holder

Global Offices: Australia ▪ Brazil ▪ China ▪ France ▪ Germany
India ▪ Italy ▪ Japan ▪ Malaysia ▪ Mexico ▪ Netherlands
Philippines ▪ Poland ▪ Portugal ▪ Singapore ▪ Spain ▪ Switzerland
Thailand ▪ Turkey ▪ United Kingdom ▪ USA ▪ Vietnam

www.faro.com
Freecall 00 800 3276 7253
info@faroEurope.com

