

PMT GAMMA

SERIES ARM

From: £16,500 +VAT

With the simple dual suspension support structure design that brings greater structural stability, the PMT GAMMA series arm is regarded as the revolutionary benchmark in the field of portable measurement. Designed with the world's first external decoupling and built-in balancing mechanism, GAMMA features high performance, great flexibility, low power consumption, reduced joint loads and ultra-long standby time, and is deemed the most stable, reliable and portable measurement machine.



Flagship
Series **GAMMA^P**

Standard
Series **GAMMA^M**

Economic
Series **GAMMA^E**

Force-Isolation Design

Drawing inspiration from the method of ‘breaking the whole into parts’, force-isolation refers to the mechanism that separates the hand grip from the scanning head in order to decouple the force between the holding pressure and the gravity of the scanning head. This helps enhance overall scanning accuracy and stability.

Optimized Structural Design

Substantial Weight Reduction

90-degree Elevated Scanning

Top Position Scanning and Wider Measurement Scope

Optimized Optical Design

More Stable Scanning Accuracy

Multiple Scanning Modes

Easily Handle Complex Scenes

Eye-protection Mode

Adjustable Laser Brightness

Advanced Thermal Management System

Keeps the Scanner in Optimal Condition

Laser Line Probe Specifications

Item		GH	GS
Accuracy		15μm	28μm
Stand-off	Far Field	220mm	
	Mid Field	157mm	
	Near Field	110mm	
Scan Width	Far Field	150mm	
	Mid Field	110mm	
	Near Field	80mm	
Depth of Field		110mm	
Max Points Per Line		4000	
Max Scan Rate		300HZ	
Point Acquisition Rate		1200000/s	
Laser Type		450nm, Class 2	
Weight		435g	

GAMMA SCANNER

Targets the Inspection of Special-shaped Workpieces to Improve Quality Control.

Choose your GAMMA blue laser scanner for your GAMMA series arm.

PMT’s GAMMA SCANNER features an optimized optical design that ensures more stable scanning accuracy. The scanning mode can easily cope with various complex usage scenarios and cover all required features. It helps solve the bottlenecks that traditional contact probes face, such as being unable to precisely measure the dimensions of massive special-shaped workpieces, while maintaining optimal function.

From: £11,500 +VAT



The PMT GAMMA 8-Axis is a complete rotary axis that can be directly connected to the GAMMA ARM. This integration enables a fully enclosed, high-accuracy add-on axis to the portable arm, saving time and effort during hardware setup. Unlike turntables, the 8-Axis is fully transparent to the measurement software and requires no software upgrades.

This innovative feature allows the real-time rotation of the workpiece relative to the measuring arm without needing to move around it. Furthermore, because the workpiece is placed on a stable platform, the GAMMA 8-Axis can inspect positions that are often difficult to reach, while significantly reducing measurement time and errors compared to manual methods.

Scan More Confidently and Quickly

An 8-axis rotary worktable offers an extended measuring range, enabling users to scan, measure and digitize features on both small and large parts using a single arm position. As a result, measuring time can be reduced by up to 40% compared to a standard 7-axis arm.

Improve Operator Efficiency

It removes the concern of measuring dead spots, ensuring minimal disruption to inspection tasks. It also helps digitize complex parts more fully and quickly.

Accelerate Subsequent Processing Tasks

Subsequent processing tasks are simplified and sped up due to the reduced number of scans that need to be aligned, as there is no need to move the measuring arm around the part or reposition the part to capture all the necessary features.

GAMMA 8-Axis

Price: £6,000 +VAT



GAMMA Measurement Range

Range	L1	L2
1.5m	375mm (14.76")	375mm (14.76")
2.0m	500mm (19.69")	500mm (19.69")
2.5m	625mm (24.61")	625mm (24.61")
3.0m	750mm (29.53")	750mm (29.53")
3.5m	875mm (34.45")	875mm (34.45")
4.0m	1000mm (39.37")	1000mm (39.37")
4.5m	1125mm (44.29")	1125mm (44.29")

SPECIFICATIONS

Accuracy - Contact Measurement (PMTArm)

GAMMA^P From: **£23,000 +VAT**

► All values represent MPE (Maximum Permissible Error)
► Contact Measurement (PMTArm): In accordance with ISO 10360-12; defined as E_{UNI} (Unilateral Error) - Distance error between two points comparing measured versus nominal. Values are +/-.

Range	¹ SPAT		² E _{UNI}		³ P _{SIZE}		⁴ P _{FORM}		⁵ L _{DIA}	
	6-Axis	7-Axis	6-Axis	7-Axis	6-Axis	7-Axis	6-Axis	7-Axis	6-Axis	7-Axis
1.5m	0.012mm	0.015mm	0.022mm	0.023mm	0.007mm	0.008mm	0.012mm	0.018mm	0.024mm	0.038mm
2.0m	0.016mm	0.018mm	0.024mm	0.025mm	0.008mm	0.010mm	0.015mm	0.019mm	0.030mm	0.042mm
2.5m	0.018mm	0.020mm	0.026mm	0.028mm	0.009mm	0.011mm	0.018mm	0.022mm	0.032mm	0.046mm
3.0m	0.026mm	0.032mm	0.038mm	0.047mm	0.012mm	0.016mm	0.025mm	0.032mm	0.045mm	0.071mm
3.5m	0.036mm	0.043mm	0.052mm	0.057mm	0.016mm	0.020mm	0.034mm	0.039mm	0.060mm	0.091mm
4.0m	0.045mm	0.054mm	0.063mm	0.073mm	0.020mm	0.026mm	0.038mm	0.044mm	0.075mm	0.112mm
4.5m	0.055mm	0.065mm	0.080mm	0.095mm	0.028mm	0.036mm	0.050mm	0.065mm	0.101mm	0.132mm

GAMMA^M From: **£20,000 +VAT**

Range	¹ SPAT		² E _{UNI}		³ P _{SIZE}		⁴ P _{FORM}		⁵ L _{DIA}	
	6-Axis	7-Axis	6-Axis	7-Axis	6-Axis	7-Axis	6-Axis	7-Axis	6-Axis	7-Axis
1.5m	0.018mm	0.020mm	0.025mm	0.024mm	0.009mm	0.011mm	0.016mm	0.020mm	0.028mm	0.043mm
2.0m	0.020mm	0.022mm	0.026mm	0.030mm	0.010mm	0.012mm	0.018mm	0.022mm	0.032mm	0.047mm
2.5m	0.023mm	0.026mm	0.029mm	0.032mm	0.012mm	0.013mm	0.022mm	0.025mm	0.037mm	0.051mm
3.0m	0.034mm	0.042mm	0.041mm	0.053mm	0.015mm	0.020mm	0.031mm	0.035mm	0.051mm	0.073mm
3.5m	0.043mm	0.055mm	0.055mm	0.066mm	0.019mm	0.024mm	0.038mm	0.043mm	0.066mm	0.094mm
4.0m	0.052mm	0.065mm	0.066mm	0.082mm	0.023mm	0.029mm	0.043mm	0.048mm	0.083mm	0.120mm
4.5m	0.061mm	0.073mm	0.089mm	0.099mm	0.038mm	0.043mm	0.078mm	0.082mm	0.108mm	0.137mm

GAMMA^E From: **£16,500 +VAT**

Range	¹ SPAT		² E _{UNI}		³ P _{SIZE}		⁴ P _{FORM}		⁵ L _{DIA}	
	6-Axis	7-Axis	6-Axis	7-Axis	6-Axis	7-Axis	6-Axis	7-Axis	6-Axis	7-Axis
1.5m	0.028mm	0.030mm	0.036mm	0.040mm	0.015mm	0.020mm	0.029mm	0.035mm	0.038mm	0.048mm
2.0m	0.030mm	0.035mm	0.040mm	0.045mm	0.018mm	0.025mm	0.035mm	0.040mm	0.041mm	0.052mm
2.5m	0.035mm	0.040mm	0.045mm	0.050mm	0.020mm	0.030mm	0.038mm	0.045mm	0.050mm	0.058mm
3.0m	0.055mm	0.060mm	0.065mm	0.070mm	0.028mm	0.035mm	0.048mm	0.050mm	0.080mm	0.091mm
3.5m	0.075mm	0.080mm	0.080mm	0.085mm	0.035mm	0.040mm	0.058mm	0.065mm	0.098mm	0.115mm
4.0m	0.090mm	0.095mm	0.100mm	0.105mm	0.044mm	0.050mm	0.068mm	0.075mm	0.116mm	0.140mm
4.5m	0.112mm	0.115mm	0.120mm	0.125mm	0.048mm	0.055mm	0.086mm	0.095mm	0.128mm	0.158mm



¹SPAT Single Point Articulation Test

²E_{UNI} Distance Error between two points comparing measured versus nominal values

³P_{SIZE} Sphere Probing Size Error comparing measured versus nominal values

⁴P_{FORM} Sphere Probing Form Error

⁵L_{DIA} Sphere Location Diameter Error (Diameter of the spherical zone containing the centers of a sphere measured from multiple orientations)



Accuracy - Contact

Measurement (PMTArm + 8-Axis)

► Contact Measurement (PMTArm + 8-Axis): In accordance with ISO 10360-12; defined as L_{DIA} (Sphere Location Diameter Error) - Diameter of the spherical zone containing the centers of a sphere measured from multiple orientations.

Range	GAMMA ^P		GAMMA ^M		GAMMA ^E	
	6-Axis+8-Axis	7-Axis+8-Axis	6-Axis+8-Axis	7-Axis+8-Axis	6-Axis+8-Axis	7-Axis+8-Axis
1.5m	0.024mm	0.038mm	0.028mm	0.043mm	0.038mm	0.048mm
2.0m	0.030mm	0.042mm	0.032mm	0.047mm	0.041mm	0.052mm
2.5m	0.032mm	0.046mm	0.037mm	0.051mm	0.050mm	0.058mm
3.0m	0.045mm	0.071mm	0.051mm	0.073mm	0.080mm	0.091mm
3.5m	0.060mm	0.091mm	0.066mm	0.094mm	0.098mm	0.115mm
4.0m	0.075mm	0.112mm	0.083mm	0.120mm	0.116mm	0.140mm
4.5m	0.101mm	0.132mm	0.108mm	0.137mm	0.128mm	0.158mm

Accuracy - Non-Contact

Measurement (PMTScanArm)

► Non-Contact Measurement (PMTScanArm): In accordance with ISO 10360-8 Annex D; defined as L_{DIA} (Sphere Location Diameter Error) - Diameter of the spherical zone containing the centers of a sphere measured from multiple orientations.

Range	GAMMA ^P		GAMMA ^M		GAMMA ^E	
	GH	GS	GH	GS	GH	GS
1.5m	0.035mm	0.040mm	0.038mm	0.045mm	0.045mm	0.050mm
2.0m	0.038mm	0.043mm	0.040mm	0.050mm	0.051mm	0.058mm
2.5m	0.042mm	0.048mm	0.045mm	0.055mm	0.057mm	0.065mm
3.0m	0.047mm	0.055mm	0.052mm	0.062mm	0.065mm	0.075mm
3.5m	0.060mm	0.068mm	0.065mm	0.076mm	0.085mm	0.095mm
4.0m	0.074mm	0.079mm	0.081mm	0.090mm	0.105mm	0.110mm
4.5m	0.120mm	0.125mm	0.131mm	0.139mm	0.150mm	0.185mm

Accuracy - Non-Contact

Measurement (PMTScanArm + 8-Axis)

► Non-Contact Measurement (PMTScanArm + 8-Axis): In accordance with ISO 10360-8 Annex D; defined as L_{DIA} (Sphere Location Diameter Error) - Diameter of the spherical zone containing the centers of a sphere measured from multiple orientations.

Range	GAMMA ^P		GAMMA ^M		GAMMA ^E	
	GH	GS	GH	GS	GH	GS
1.5m	0.035mm	0.040mm	0.038mm	0.045mm	0.045mm	0.050mm
2.0m	0.038mm	0.043mm	0.040mm	0.050mm	0.051mm	0.058mm
2.5m	0.042mm	0.048mm	0.045mm	0.055mm	0.057mm	0.065mm
3.0m	0.047mm	0.055mm	0.052mm	0.062mm	0.065mm	0.075mm
3.5m	0.060mm	0.068mm	0.065mm	0.076mm	0.085mm	0.095mm
4.0m	0.074mm	0.079mm	0.081mm	0.090mm	0.105mm	0.110mm
4.5m	0.120mm	0.125mm	0.131mm	0.139mm	0.150mm	0.185mm

Hardware Specifications



Operating Temp Range: 5°C - 45°C (41°F - 113°F)



Temp Rate: 3°C/5mins (37.4°F/5mins)



Operating Humidity: 0-95%, non-condensing



Weight: 8.8kg to 10.6kg



Battery Life: 16h+ for one battery;32+ for two batteries (base on contact measurement)



Power Supply: Universal worldwide voltage; 100-240VAC; 50/60Hz



Data transmission mode: USB or Wi-Fi



Complete Measurement Solutions

Equipment Sales, Hire & Leasing | Subcontract Inspection | Laser Scanning & Reverse Engineering
Alignment & Inspection | Robot Calibration & Floor Marking | 3D Printing | Training & more

Contact us on **0161 637 8744** to find out more or to place an order.

Manchester Metrology Ltd

Unit 3, The Wellington Centre, Whitelands Road, Ashton-under-Lyne OL6 6UY
0161 637 8744 | manchester-metrology.co.uk

