

8200 Super Heavy Tilt Tandem Axle Trailer

All aluminum construction (excluding axle & coupler)

<u>Model</u>	<u>Weight</u>	<u>Bed Size</u>	<u>Tires</u>
8220-14K-TILT-4SF-TA-EL-RTD	2,650#	80.5" x 238" (73.75" x 190")	16"
8222-14K-TILT-4SF-TA-EL-RTD	2,750#	80.5" x 258" (73.75" x 209")	16"
8222-14K-TILT-6SF-TA-EL-RTD	2,750#	80.5" x 258" (73.75" x 186")	16"

Standard Equipment

- 2) 7000# Rubber torsion axles - Easy lube hubs
- Electric brakes, breakaway kit
- ST235/80R16 Radial tires
- Aluminum wheels, 8-6.5 BHP
- Removable aluminum fenders
- Extruded aluminum floor
- 5 1/2" Bump rail
- A-Framed aluminum tongue, 56.5" long with 2-5/16" adjustable coupler
- Stake pockets and rub rail
- 6) Bolt-on heavy tie downs
- 10K Spring-loaded drop leg jack
- LED Lighting package, safety chains
- Loading angle: 12° / 11.5° / 12.5°
- Width between fenders = 82.25"
- Overall bed width on stationary front = 79.125"
- Overall width = 101.5"
- Overall length = 288" / 308" / 308"



Options

<u>Part #</u>	<u>Description</u>
20-0001626	Package, 8200-14K-TILT Airdam
50-0004765	U-Channel 4.0625" x 1.8125" x .25" x 2.50" - Lg. Stake Pocket
60-0000679	Tie Down, Bolt-On Heavy 14K
40-0000060	Spare Tire Carrier Package, Side Mount 8200-14k
60-0001496	16" Tire, Silver Eagle Aluminum 8 bolt
20-0001602	Package, Storage Box 14K Series