

5410T Tilt Utility Trailer

All aluminum construction (excluding axle & coupler)

<u>Model</u>	<u>Weight</u>	<u>Bed Size</u>	<u>Tires</u>
5410TILT-S	360#	4'6" x 10' (54" x 120")	13"

Standard Equipment

- 2000# Rubber torsion axle - No brakes - Easy lube hubs
- ST175/80R13 Radial tires
- Aluminum wheels, 5-4.5 BHP
- Aluminum fenders
- Extruded aluminum floor
- 6" Extruded front retaining bumper
- 3" Formed aluminum tongue, 48" long, 2" coupler, riser for proper hitch height
- 4) Stake pockets (2 per side)
- 4) Tie down loops (2 per side)
- Tongue Handle
- Receptacle Holder
- Fender Steps
- Swivel tongue jack, 1200# capacity
- LED Lighting package, safety chains
- Overall width = 75.5"
- Overall length = 168"
- Gas cylinder to raise bed for loading
- 15° tilt



Options

<u>Part #</u>	<u>Description</u>
50-0000463	Pocket Stake Utility 2.500"
50-0003658	Loop Tie Down .625" x 8"
60-0000650	2000# RTD Stainless Steel Small
20-0000003	Tire Carrier Spare 4" Vertical 5 Bolt
60-0001488	13" Tire, Silver Eagle Aluminum

Side rack and front rock guards are not available for 5410TILT model