

Boat Manufactured By:

Manitou

7800 Northport Drive • Lansing, MI 48917
(517) 322-3822
www.manitoupontoonboats.com

MANITOU 25 LEGACY SL

Length	26' 8"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	4,160 lbs
Maximum HP	600 hp
Fuel Capacity	90 gal
Pontoon # / Diameter	3 / SHP
Weight as Tested	6,043 lbs

F200XCA / LF200XCA

Horsepower	200 hp
Induction	EFI/VCT/DOHC
Displacement	2.8L
Weight (Estimated)	489 lbs
Gear Ratio	1.86:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Reliance® Series
Diameter x Pitch	14-1/4 x 18
Yamaha Part #	68F-45978-20-00 / 68G-45978-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	72° F / 78° F
Elevation (in feet above sea level)	1005'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 45 gallons of fuel, 3 batteries, safety and test equipment.

YPB#: PB_MAN_25 Legacy SL_TW_F200XCA_7.28.20_PNT



Engine: Yamaha F200XCA / LF200XCA

Boat: Manitou 25 Legacy SL

Configuration: Twin

Test Date: 27-Jul-2020



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.4	1.6	3.48
1500	7.6	2.7	2.87
2000	12.1	4.3	2.84
2500	18.1	6.1	2.96
3000	22.9	7.7	2.99
3500	27.9	9.9	2.82
4000	32.7	13.9	2.36
4500	38.5	17.6	2.18
5000	43.1	22.6	1.91
5500	46.9	30.3	1.55
6100	51.1	37.4	1.37
0-20 MPH: 4.06 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.