



SSS-5689

Make: CMI

Size: Factory Rated @ 300 TPH

Type: Portable Parallel Flow Drum Plant

DESCRIPTION: Complete CMI Portable Parallel Flow Drum Plant. Features of this plant include the following:

- Portable CMI Model #PF422 Four (4) Bin 8' x 13' Cold Feed System with nominal 30" wide feeders. Bins #1 and #4 each have 5 HP drives and bins #2 and #3 each have 3 HP drives. Bin #1 has a reversing feeder conveyor for use with different materials. A nominal 30" wide x nominal 90' long integral collecting conveyor with bi-folding head section and 15 HP drive. This cold feed system is also equipped with self-storing, retractable support skids to grade, 18" bin extensions, and tandem axle portability. One additional stationary Cold Feed Bin with 24" wide x 9' long feeder conveyor. 15hp drive Collecting Conveyor included.
- CMI 4' x 10' single deck Virgin Aggregate Scalping Screen with adjustable support legs to grade.
- One (1) CMI Model #SE3047 Portable self-erect 30" x nominal 47' long Virgin Scale Conveyor with receiving trough, belt scale and wind guards on a single axle suspension.
- Portable CMI Model UVM-1700 Parallel Flow Drum. The drum is 8'-6" diameter through the main body with 9'-6" expanded ends x 38' long and is equipped with a 5 HP slinger feed conveyor. The unit is cradle chain driven with a single 100 HP motor and Heavy-Duty Dodge TDT-10 reducer. A Hauck Starjet 580 burner, a recycle entry collar, support stands to grade, and a quad axle suspension.
- Meeker complete Dust Runaround System features a 700BBL Dust Silo with weigh pod & surge pod. Pod to Pod weigh depleted dust runaround system. 3HP Rotary Air Lock. High Level Indicator. 40HP Dust Blower. Access Ladder, from grade to top of silo
- Portable CMI, Model RA-318P Roto-Aire Baghouse includes mounted fan with twin 100 HP drive motors, an integrally mounted inertial collector, bottom mounted twin auger dust removal with cross auger and tandem axle suspension.
- CMI 25,000 Gallon Portable, Direct Fired AC Tank with a mounted AC unloading pump, an AC metering system, on board diesel storage tank, blocking pads and a tandem axle suspension.
- Stationary 30,000 Gallon Coiled Only w/ mounted CEI Model #CEI-1500 1.5mbtu Hot Oil Heater.
- Portable 20,000 Gallon Burner Fuel Tank w/ Hy-Way® Electric Pre-Heater Model #PI-962T-9
- Stationary Calibration Tank
- CMI/Caterpillar Model PRB-120 Portable Self-Erect RAP System includes a single 8' x 14' bin with a 30" feeder conveyor, a dual roll lump breaker with 10 HP drives, and an inclined 24" scale conveyor all mounted on a single axle frame.
- Two (2) Bin Recycle System. The bin opening at the top is a nominal 8'-6" x 14' with steep sidewalls. 30" x nominal 10' long Feeder Belts. Each bin contains a grizzly and air cannon. 36" x nominal 60' long Collecting Conveyor with Belt Scale and Gravity Take-Up.



SSS-5689

- CMI Model SE-653S self-erecting silo system with an onboard gasoline powered hydraulic lifting system. 65 Ton capacity, reverse weigh silo with batcher assembly. 36" wide main slat conveyor with a 60 HP drive and is also equipped with a reject gate. Mounted on the gooseneck is a Gardner Denver 40HP Air Compressor. Silo System is equipped with a tandem axle suspension.
- One (1) CMI Control House with MCC that includes EZ Blend Blending Plant Controls, Libra Loadout Controls and Hauck Burtner Controls.



AVAILABILITY, PRICE, AND CONDITION SUBJECT TO CHANGE BY STANSTEEL®. SPECIFICATIONS ARE ACCURATE TO OUR KNOWLEDGE; HOWEVER, THEY ARE NOT GUARANTEED. ALL PRICES ARE IN U.S. DOLLARS UNLESS OTHERWISE NOTED. EQUIPMENT IS SOLD ON THE BASIS OF AS IS, WHERE IS, THEREFORE, STANSTEEL® RECOMMENDS INSPECTION BY THE BUYER OF ANY USED EQUIPMENT TO DETERMINE SUITABILITY TO THEIR REQUIREMENTS.