

CONTAMINEX
Certification Sheet

VOITH, INC.
2620 E. Glendale
Appleton, WI 54915
Tel (414) 731-7724
Telefax (414) 731-0240

IDENTIFICATION	CUSTOMER	VOITH, INC.		SIZE & TYPE	CMS 10	
	ADDRESS (ORDER)	APPLETON, WI		SERIAL NO. (S)*	3144	
	ADDRESS (INSTALL)	SAME		VOITH JOB NO.	Y91-7777 (old #)	
	CUST. ORDER NO.	ACUM1003		ORDER DATE	1-1-91	
	CUST. EQUIP. NO.			MOTOR EQUIP. NO.		
	CERTIFIED BY	 ROBERT J. MATZ, P.E.		TITLE	MANAGER OF ENGINEERING, S.P. DIV.	
APPLICATION	INSTALLATION DWG.	D29-130023		STOCK TO BE HANDLED	ALL	
	STOCK CONSISTENCY	3.5 - 4.0 %BD		PULPER THROUGHPUT	48 BDSTPD	
	PULPER SIZE:	212 / 8.22 CU FT/FT DIA.		PULPER EXTRACTION HOLE DIA.	N/A	
	OUTLET CONNECTED TO:	☐ VIBRATION SCREEN		☐ SCREEN DRUM		
DRIVE	IMPELLER SPEED	294357 RPM		POWER REQUIREMENT	38 HP	
	MOTOR SHEAVE	4 GR 8.00 O.D.		BORE	2.375 KW .625 X .313	
	DRIVEN SHEAVE	4 GR 31.50 O.D.		BORE	85 MM KW 22MM X 9MM DP	
	BELT PULL	≈ 21.5 LBS.		NO. & SIZE OF BELTS	1 - 4/5VX1400	
	CENTER DIST.	37.10		SERVICE FACTOR	1.5	
MOTOR	MOTOR: HP	50 RPM 1200		FRAME SIZE	365T VOLTS 460	
	PHASE	3 HERTZ 60		MOTOR SHAFT DIA.	2.375	
OPTIONS	FURNISHED ONLY IF MARKED					
	☒ V-BELT DRIVE		☒ GUARD		☐ DISCHARGE VALVE	
REMARKS	☐ CONTROL PANEL CONTROL S/N _____					
	*ALWAYS SPECIFY UNIT SERIAL NO. WHEN ORDERING SPARE PARTS					
	Screen plates available					
	6 mm					
	10 mm					
	Sheaves PR 8.0		DRIVEN 21.2		Motor 1160 RPM	
						Driven Speed 438