



|  |                          |                         |
|--|--------------------------|-------------------------|
| <b>CAPACITY LITERS</b> <u>          <b>43.900</b>          </u>          | <b>SHELL SIDE</b>        | <b>JACKET/COIL SIDE</b> |
| Design Pressure KG/cm2   | 4/VAC.                   |                         |
| Design Temperature °C  | 80                       |                         |
| Material   | AISI 304                 |                         |
| ANCC or ISPESEL certification: <u>          <b>CA 2159</b>          </u> | <b>NOZZLE DIMENSIONS</b> |                         |
| Availability in stock n° <u>          <b>01</b>          </u> units      | <b>Pos</b>               | <b>Service</b>          |
| <b>MANUFACTURER:</b> <u>          <b>COSMIN 1968</b>          </u>       | A                        | Man hole                |
| <input checked="" type="checkbox"/> USED                                 | B                        | Product inlet           |
| <input type="checkbox"/> USED RECONDITIONED                              | C                        | Product outlet          |
| <input type="checkbox"/> UNUSED  | D                        | Spare nozzle            |
| <b>WEIGHT (approx) Kg</b> <u>          <b>14160</b>          </u>        | E                        | Vacuum                  |
|  | <b>NOTE</b> _____        |                         |