


Part of the Atlas Copco Group


DF135C

Tracked pavers



Technical data





Dimensions	DF135C
Basic width	2.55 m
Working width, maximum (incl. extension boxes)	9 m
Working width, minimum (with reducing shoe)	2 m
Masses	
Weight	18.50 t
Capacity	
Placement thickness (max)	300 mm
Theoretical placement capacity	750 t/h
Practical placement capacity	
Undercarriage	
Crawler length	2,900 mm
Crawler width	305 mm
Final drive	Hydrostatic direct drives comprising planetary gear units and hydr. oil motors integrated in crawler track frame
Material hopper	, <u> </u>
Capacity	6.0 m ³
Capacity	13 t
Capacity	6.0 m³ (13 t)
Dumping height, center	520 mm
Dumping height, outside	605 mm
Dumping height (center/outside)	520 mm /605 mm
Traction	
Paving speed	0-23 m/min
Transport speed	4.50 km/h
Engine	
Manufacturer/Model	Deutz TCD 2013 L06
Rated power, SAE J1995	140 kW (190.0 hp) @ 1,800 rpm
Emissions according to	EU 3A/Tier 3
Electrical system	24V
Conveyor	
Conveyor type	Dual bar feeder
Conveyor width	600 mm
Conveyor control	Proportional speed control. Left and right augers to be controlled separately. Reversible direction of rotation.
Auger	

Auger control Proportional speed control.

Left and right augers to be controlled separately.

Reversible direction of rotation.

Service kits

Service kit #29