

Transducers for Vetus 9



Probe	Illustration	Type of Array	Parameters	Application	Biopsy kit
C11-3s		Curved	- Bandwidth: 2.6 – 12.8 MHz - Extended FOV: 113° - Convex Radius: 15 mm	Abdomen (Canine, Feline), Reproduction (Canine, Feline), Small Parts (Canine, Feline)	NGB-018, available, multi angle, reusable
SC6-1s		Curved	- Bandwidth: 1.2 – 6.0 MHz - Extended FOV: 72° - Convex Radius: 60 mm	Abdomen (Canine, Equine, Bovine, Ovine, Camel, Alpaca), Reproduction (Canine, Equine, Bovine, Ovine, Camel, Alpaca)	NGB-022, available, multi angle, reusable
L13-3Ns		Linear	- Bandwidth: 3.0 – 13.0 MHz - Field of View (max): 38.0 mm	Abdomen (Canine, Feline), Small Parts (Canine, Feline), Ocular (Canine, Feline), MSK (Equine, Camel)	NGB-053, available, multi-angle, reusable
L20-5s		Linear	- Bandwidth: 6.0-23.0 MHz - Field of View (max): 28.5mm	Abdomen (Canine, Feline), Ocular (Canine, Feline), MSK (Canine, Feline)	None
L16-4Hs		Linear	- Bandwidth: 3.5-16.0 MHz - Field of View (max): 25.3mm	Abdomen (Canine, Feline), Ocular (Canine, Feline), MSK (Canine, Feline, Equine)	None
P8-2s		Phased	- Bandwidth: 2.3 – 8.0 MHz - Field of View (max): 90°	Cardiology (Canine, Feline), Abdomen (Canine, Feline)	None

Probe	Illustration	Type of Array	Parameters	Application	Biopsy kit
P10-4s		Phased	• Bandwidth: 3.0 – 11.4 MHz • Field of View (max): 90°	Cardiology (Canine, Feline), Abdomen (Canine, Feline)	None
SP5-1s		Phased	• Bandwidth: 1.5 – 4.5 MHz • Field of View (max): 90°	Cardiology (Canine, Equine, Bovine, Ovine, Camel, Alpaca)	NGB-011, available, multi-angle, reusable

