

REV. NO.	ITEM	QTY	DESCRIPTION	MATERIAL	NOTE	UNIT WEIGHT	TOTAL WEIGHT	WHSE	SUPPLIER	DEL'Y DATE	P.O. NUMBER	P.O. DATE	UNIT PRICE	TOTAL PRICE	REMARKS
	RO-410	1	1/4" ORIFICE UNION c/w 9/64" ORIFICE, C.S.			1	1								
	TC-2257	2	KIMRAY HT-12 TEMPERATURE CONTROLLER BASE ASSEMBLY:			8	16								
	TSH-2257		-30°F TO 750°F TEMPERATURE RANGE c/w KIMRAY 1"-SS-12 316SS												
			SEPERABLE SOCKET, SWEET I/G												
	TI-2257	1	GAUGETECH GT3 TEMPERATURE INDICATOR: 3" DIAL, 9" STEM,			1.5	2								
			50/500°F TEMP. RANGE, DUAL SCALE												
	TI-2259	1	GAUGETECH GT3 ADJUSTABLE ANGLE MOUNT TEMPERATURE INDICATOR:			1.5	2								
			5" DIAL, 9" STEM, 50/500°F TEMP. RANGE, DUAL SCALE												
	TI-2210	1	GAUGETECH GT3 TEMPERATURE INDICATOR: 3" DIAL, 12" STEM,			1.5	2								
			-40/160°F TEMP. RANGE, DUAL SCALE												
	TI-2270	1	GAUGETECH GT3 TEMPERATURE INDICATOR: 3" DIAL, 9" STEM,			1.5	2								
			0-250°F TEMP. RANGE, DUAL SCALE												
	TW-2257	3	1/2"-FNPT x 3/4"-MNPT x 9" LG. 316SS THERMOWELL			2	6								
	TW-2259		(U-LENGTH = 7 1/2") 0.216" BORE												
	TW-2270														
	TW-2210	1	1/2"-FNPT x 3/4"-MNPT x 12" LG. 316SS THERMOWELL			2	2								
			(U-LENGTH = 10 1/2") 0.216" BORE												
						2									
	TH-2257	1	SENTINEL 8-10A THIEF HATCH; 16 oz. PRESSURE; 0.40 oz. VACUUM RELIEF;			25	25								
			GASKETS AND BOLTING; SOUR SERVICE												
	XV-2220	1	1" NPT FISHER D4 CONTROL VALVE AND ACTUATOR: 3/4" DIA. PORT,			17	17								
			FAIL OPEN, BENCH SET AT 0-30 PSIG FOR												
			3750 PSIG SHUTOFF, NACE SERVICE, SWEET I/G												
	XYV-2220	1	1/4" NPT ASCO EF8320G200 SOLENOID VALVE, 24VDC, CLASS I DIV I, X.P.,			5	5								
			UNIVERSAL 3-WAY OPERATION, 60 PSIG MWP, STANDARD MATERIALS												
			TOTAL PAGE WEIGHT (Lbs.):				78								
NOTES: *** SEE NOTE COLUMN FOR APPLICATION NUMBERS *** 1. MATERIAL TEST REPORTS ARE REQUIRED.					BY:	RKL		ALCO  GAS & OIL PRODUCTION EQUIPMENT LTD. BILL OF MATERIALS SOUR GLYCOL DEHYDRATION UNIT - 24" O.D. CONTACTOR w/ 375,000 BTU/HR. REBOILER							
					DATE:	Oct. 4, 2004									
					CHK'D										
					CHK'D										
					APP'D:										
					CUSTOMER: DEVON CANADA CORP. C/O ASHER ENGINEERING LTD. LOCATION: SEPTIMUS COMP. STATION										
					L.S.D.: 9-36-81-19 W6M		DWG/SHOP ORDER:		B-2004-7269-50B-006/010				REV. 0		

BOM_Hookup.xlt (rev.1d)

NOTE: ONE (1) UNIT REQUIRED.

[illegible]

REV. NO.	ITEM	QTY	DESCRIPTION	MATERIAL	NOTE	UNIT WEIGHT	TOTAL WEIGHT	WHSE	SUPPLIER	DEL'Y DATE	P.O. NUMBER	P.O. DATE	UNIT PRICE	TOTAL PRICE	REMARKS
	GL-818	2	1 1/2" NPT OMB MODEL #837F GLOBE VALVE: CLASS 800, 1975 PSIG @ 100°F REGULAR PORT, FORGED STEEL, SOUR SERVICE, NACE			7.5	15								
	GL-818	1	1" NPT OMB MODEL #835F GLOBE VALVE: CLASS 800, 1975 PSIG @ 100°F REGULAR PORT, FORGED STEEL, SOUR SERVICE, NACE			3.6	4								
	GL-816	6	1" SW OMB MODEL #835T GLOBE VALVE: CLASS 800, 1975 PSIG @ 100°F REGULAR PORT, FORGED STEEL, SOUR SERVICE, NACE			3.6	22								
	GA-816	2	2" SW OMB MODEL #818T GATE VALVE: CLASS 800, 1975 PSIG @ 100°F REGULAR PORT, FORGED STEEL, SOUR SERVICE, NACE			8.5	17								
	GA-816	17	1" SW OMB MODEL #815T GATE VALVE: CLASS 800, 1975 PSIG @ 100°F REGULAR PORT, FORGED STEEL, SOUR SERVICE, NACE			3.5	60								
	GA-818	1	1" NPT OMB MODEL #815F GATE VALVE: CLASS 800, 1975 PSIG @ 100°F REGULAR PORT, FORGED STEEL, SOUR SERVICE, NACE			3.5	4								
	GA-808	2	1" NPT OMB MODEL #815F GATE VALVE: CLASS 800, 1975 PSIG @ 100°F REGULAR PORT, FORGED STEEL, STANDARD SEVICE			3.5	7								
	NE-6008	9	1/4" NPT AGCO H7VIC-2 NEEDLE VALVE: A-105 BODY; STD TRIM			1.3	12								
	NE-6008	2	1/2" NPT AGCO H7VIC-4Q NEEDLE VALVE: A-105 BODY; STD TRIM			1.3	3								
	NE-6018	4	1/4" NPT AGCO H7VIS-2-SG NEEDLE VALVE: 316SS BODY; SOUR SERVICE			1.3	5								
	NE-6018	6	1/2" NPT AGCO H7VIS-4Q-SG NEEDLE VALVE: 316SS BODY; SOUR SERVICE			1.3	8								
	NE-6019	3	1/2" FNPTxMNPT AGCO H7VIS-44Q-SG NEEDLE VALVE: 316SS BODY; SOUR SERVICE			1.3	4								
	BB-6019	1	3/4" MNPT x 1/2" FNPT AGCO M5VIS-46-SG MULTI-PORT GAUGE VALVE: 316SS BODY; SOUR SERVICE			2.5	3								
	STR-2250	2	1/2" NPT ALTA YS 600 Y-STRAINER; 1480 PSIG @ 100°F; 1/32" PERFORATED SCREEN; STD MAT'LS			3	6								
	STR-2257	1	1" NPT ALTA YS 600 Y-STRAINER; 1480 PSIG @ 100°F; 1/32" PERFORATED SCREEN; STD MAT'LS			5	5								
	STR-2240	2	2" SW ALTA YS 600 Y-STRAINER; 1480 PSIG @ 100°F; 1/32" PERFORATED SCREEN; STD MAT'LS			16	32								
			TOTAL PAGE WEIGHT (Lbs.):				204								
NOTES: *** SEE NOTE COLUMN FOR APPLICATION NUMBERS *** 1. MATERIAL TEST REPORTS ARE REQUIRED.						BY:	RKL	ALCO GAS & OIL PRODUCTION EQUIPMENT LTD. The information contained herein is the confidential property of ALCO Gas & Oil Production Equipment Ltd., and is not for publication. The information is issued on the understanding that no part thereof shall be copied or communicated to a third party without authorization in writing from ALCO Gas & Oil Production Equipment Ltd. BILL OF MATERIALS SOUR GLYCOL DEHYDRATION UNIT - 24" O.D. CONTACTOR w/ 375,000 BTU/HR. REBOILER CUSTOMER: DEVON CANADA CORP. C/O ASHER ENGINEERING LTD. LOCATION: SEPTIMUS COMP. STATION							
						DATE:	Oct. 4, 2004								
						CHK'D									
						CHK'D									
						APP'D:									
NOTE: ONE (1) UNIT REQUIRED.						L.S.D.: 9-36-81-19 W6M		DWG/SHOP ORDER:		B-2004-7269-50B-008/010		REV. 0			
BOM_Hookup.xlt (rev.1d)															

[illegible]

[illegible]