

Options CMZ TTL 52-52-T1Y-T2Y (2020)

Machine language: English

Machine Manuals in pdf format available for download in cloud.cmz.com

Fanuc G codes type A

Coolant through right spindle

Tailstock in right spindle (Short Version) for MT no.3 rotating center (not supplied)

Removable tool presetter

Side exit chip conveyor (standard type)

Upper turret (T1) High Pressure coolant pump with 3 programmable settings (35, 15 & 6 bar). Includes a 75 µm replaceable filter

Lower turret (T2) High Pressure coolant pump with 3 programmable settings (35, 15 & 6 bar). Includes a 75 µm replaceable filter

Coolant wash gun

Oil skimmer

Coolant chiller

Machine status indicator light

Tool life management function

Tool load monitoring function

Pneumatic, automatic, programmable parts catcher

Pneumatic parts catcher will be equipped with a gripper that pneumatically opens/closes to clamp the part to be ejected

Pneumatic parts catcher will be equipped with a catcher box that pneumatically opens/closes to catch the ejected part

Pneumatic parts ejector for subspindle with adjustable stroke of 100mm & end of stroke conformation

Barfeed interface - Unimag

Interface for mist collector tube Ø150mm

Hainbuch TOPplus Mini 52 pullback collet chuck for main spindle

Hainbuch TOPplus Mini 52 deadlength collet chuck for subspindle