



TF-200Q

Fully Automatic Tray Former



IPak's Model TF-200Q fully automatic tray former is designed and built to withstand the rigors of continuous, heavy-duty, industrial applications. The TF-200Q will form regular slotted trays in various configurations including four corner glued trays, one and two piece telescoping trays, and variations of self-locking trays suitable for most any application including agricultural, food processing and distribution. It will continuously operate at speeds of up to 35 trays per minute and is capable


of forming a wide range of tray sizes. Size changes are quick and easy, performed in less than 10 minutes due to its quick size change features. If your application requires specialty or complex tray styles, consult your factory representative regarding IPak's TF-200 Series of specialty tray formers. Like all IPak machinery, the TF-200Q is known for reliability and dependability and is backed by IPak's friendly and knowledgeable service team.

TF-200Q Fully Automatic Tray Former

Standard Features


- All mechanical drive train
- Easy load hopper
- Piab type vacuum pick system
- Offset dual vacuum cam design
- Quick size change features
- Corrosion resistant construction
- Remote Demand Controlled
- All controls 24 Volts DC
- Programmable Controller
- Fully interlocked safety guarding

Machine Specifications



- Machine weight: 2800 lbs. (1270 kg)
- Machine length (typical): 10'6"
- Air: 1.0 cubic feet per cycle at 80 p.s.i.
- Electrical: 230 (460 optional) Volts AC, 3 phase, 60 Hz
- Speeds up to 35 trays per minute
- PLC operated sequence and timing control
- NEMA 12 control panel
- Nordson hot melt adhesive system
- Lock-out / tag-out compliant


Some Examples of Trays Formed on the TF-200Q



Optional Features

- Large capacity glue system
- Left or right hand controls
- Custom voltages
- Modifications for under or oversize cases
- High speeds – over 35 trays per minute
- Choice of hot melt glue systems
- Low hopper sensor
- Motorized out feed conveyor

Forming Sequence



Method of Operation

The TF-200Q hopper is loaded with die cut blanks. Vacuum cups pull the blanks onto the lug and chain drive. Hot melt adhesive is applied, then the blank is impacted and folded by a forming mandrel, compressed, and ejected upright onto a conveyor ready for filling.

The IPak Product Line Includes:

Tray Formers	Flange Sealers
Case Sealers	Stackers and De-Stackers
Sleeve Wrappers	Custom Applications



a division of Pro Mach 

IPak Machinery,
Wexxar Packaging Inc.
#1-14211 Burrows Road
Richmond, BC Canada V6V 1K9

Tel: 604-940-8073
Fax: 604-940-8074
email: sales@ipakmachinery.com
www.ipakmachinery.com