

835 *Flex Case Packer*

raising the standard for flexibility and reliability



benefits

- Gentle and flexible handling of variety of products and formats
- Quick and simple, no tool changeover
- Superior case handling through use of electric lug chain
- AB Panelview 600 as standard operator interface
- High speed laner allows for integrated handling of difficult containers
- Large options package
 - Air transfer system*
 - High speed laning*
 - Positive placement packing for delicate containers*
 - Stainless steel frame*
 - Bottle turner*
 - Reverse feed*
 - Flap opening and control*

The Hartness Model 835 Flex raises the standard for flexibility and reliability in medium speed, vertical case packing. Engineered versatility is the heart of the system. The machine's broad options package gives it the flexibility to handle a wide range of container types, shapes and materials. Glass, plastic, cans and paperboard in round and non-round configuration, and ranging in size from 2 ounces to 2 1/2 gallons, are all easily handled in the Model 835 Flex. Depending on size, containers can be packed in multiple tray or case configurations for increased throughput speed. An integrated high speed laner option ensures integrated responsibility for the laning and conveying of difficult shaped bottles. The air transfer option allows for the case packing of a variety of difficult shaped containers including reverse tapered bottles, flasks, chimed cans, and trigger bottles.



HARTNESS
INTERNATIONAL

packaging solutions made innovatively simple

835 Flex Case Packer

general specifications

item	description
machine	Model 835 FLEX
speed	Up to 30 cases per minute
container application	Round and non-round containers glass (Returnable and one-way) Pet (prb and one-way)
case application	HSC, RSC (newly erected or “reshippers”) Full, 1/2 and 1/4 depth plastic crates
weight	Approximately 6,000 lbs (2720kg)
case dimensions	Length: 7-22.5 in [177.8-571.5mm] Width: 5.5-16.5 in [139.7-419.1mm] Height: 2-20 in [50.8-508mm]
voltage	240 / 460 AC or customer choice
phase	3
hz	50 / 60
amp	30 / 15-amp minimum electrical service recommended
air consumption	Ware strip-1.0 CF/cycle Air transfer-2.1 CF/cycle

HARTNESS
INTERNATIONAL

1200 Garlington Rd
PO Box 26509
Greenville SC 29616-1509
phone: 864.297.1200
fax: 864.297.4486
email: info@hartness.com
www.hartness.com

The dimensions, descriptions, illustrations and other particulars in this profile are given in good faith but are not intended to and do not constitute any guarantee or warranty given by Hartness International or form any part of any contract. Photographs and/or illustrations may be shown with optional equipment or without safety guards in order to show features. Hartness International designs are covered by numerous US and International Patents.

