



The Dupps Company

P.O. BOX 189
GERMANTOWN, OHIO 45327-0189
TELEPHONE: 513/855-6555
FAX: 513/855-6554

Manufacturer of Process Machinery

CONFIGURATION SHEET - DUPPS DEWATERING PRESS

DATE: March 21, 1995 SERIAL #: C80-235808

SOLD TO: ANDRITZ-RUTHNER, INC. P/N: 0E-45391-001
FOR: STONE CONSOLIDATED
DIV. LAURENTIDE MODEL #: 3624B
GRANDMERE, QUEBEC, CANADA

APPLICATION:

DRY WEIGHT: 55,000 lbs.

MATERIALS OF CONSTRUCTION

Feed Hopper: 316L Cplg Guard: Fiberglass Disch Box: 316L
Belt Guard: Fiberglass Cages: 316L Liquid Pan: 316L
Shaft: 316L Choke: 316L

PRESS SHAFT

Serial #94-1044 National Board #2184 Min Wall: 3/8"
CRN #C9063.65

Compr Ratio: 1.75:1 Shaft Wgt: 6,900 lbs. Plug Length: 12

Max Speed: 1.6 RPM Replacement Disch Flight #: 131806

Wear Shoes Material: 17-4PH P/N: 120856

CAGES

Primary Qty: 3 Mat'l: 316L P/N: 128763
Intermed Qty: 1 Mat'l: 316L P/N: 128764
Backup Screen: Mat'l: 316L P/N: 120545
Discharge Qty: 1 Mat'l: 316L P/N: 128767
Backup Screen: Mat'l: 316L P/N: 120548

CAGE SCREENS (Inner)

Primary
Hole dia: 1/8" Mat'l: 316L Open Area: 13% P/N: 119365
Intermed
Hole dia: 1/8" Mat'l: 316L Open Area: 13% P/N: 119365
Discharge
Hole dia: 1/8" Mat'l: 316L Open Area: 13% P/N: 119365



FEED HOPPER

Hole dia: 1/8" Mat'l: 316L Open Area: 13% P/N: 119365

CHOKE

Wear Face Part #: 126550

MOTOR

HP: 50 SPEED: 1800 FRAME SIZE: 324T/326T

DRIVE SHEAVES:

Driver: 3R5V85 3GRV	P/N: 121382	Bushing: R1 2-1/8"	P/N: 110519
Driven: 3R5V118 3GRV	P/N: 121384	Bushing: R1 2"	P/N: 107695
Belts: 3-5VX1320	P/N: 121383		

DRIVE COUPLING:

Mfr: ZURN Model: 209 FA P/N: 130466

COVER CONSTRUCTION: 316L

NOTES:

SENSOR MTG. XSA V11151, P/N #132709

REDUCER "U" FRAME SHIPPED LOOSE
