

OILWELL E-2000 DIESEL ELECTRIC

(20,000 foot rating)

OILWELL E-2000 single drum 2000 hp. Draw works (s/n H47-1600) with ELMAGCO 7838 electric brake (s/n TA-11138W), PERMA brake lubrication device, FOSTER catheads, ROSS HILL Drillers console and powered by (2) 1000 hp. GE 752 electric motors. (Inspected)

LEE C MOORE 142' x 30' base +31' high beam leg raised floor cantilever type Mast having a rated static hook load capacity of 1,300,000 lbs per API standard 4E with 14 lines strung to the traveling block. 800 ton skewed type Crown block having one 60" diameter fabricated steel fast line sheave and seven 60" diameter fabricated steel working sheaves mounted on tapered roller bearings. Deadline on off drillers side. Sheaves grooved for 1 1/2" diameter Wireline. (s/n T3844)

LEE C MOORE swing up substructure. 30' floor height, 26' clear height, 1,300,000 lb casing capacity simultaneous with 800,000 lb. setback capacity at 31 foot elevation. (s/n 73844)

(2) OILWELL A-1700 PT triplex mud pumps rigged out with pulsation dampeners, pressure relief valves, electric oilers and each powered by (2) GE 752's.

ROSS HILL model 1400, 4 bay SCR (s/n 5620-2) (rebuilt)

OILWELL 500 ton block (s/n 020-026) with BJ 5500 dynaplex hook (s/n 931)

NATIONAL P-650 swivel (s/n 651-10)

CANRIG 500 ton model 1050E with control house.

NOV 3080 iron ruff neck

OILWELL 27 1/2" rotary table (s/n 688)

page 2

KOOMEY 180 gal 7 station air and electric accumulator with remote.
(s/n 2503)

(3) CATERPILLAR D399TA's (s/n's 35B5830, 35B1797, 35B6320) each with KATO 1050 kW generators, oversized radiators, cold start LISTER diesel powered air compressor, and (2) SULAIR screw type electric air compressors (Ran out CAT dealer)

(3) Mud tanks with stirrers, shaker, electric centrifugal pumps, de sander, de silter, cyclone, SWACO mud de gasser.

10' x 45' pusher house

Junk box with misc., 25 lift subs, 15 crossover bit subs, mud bucket, Kelly Drive bushing, elevator bails, solid master bushing, 13 5/8 5000 drilling spool, vibrator hose, Kelly valves, dart valves.

Trip tank, oil bin, catwalk V-door, driller doghouse, ODS doghouse, mud mixing house, fuel tank, derrick stand, (3) water tanks, suitcases, survey unit, combination storage house, pump parts house liners rods etc. Hand rails, shaker screen box.

OILWELL E 2000HP

OILWELL E-2000 single drum draw works with Elmagco 7838 electric brake and (2) GE 752's

LEE C MOORE cantilever mast 142' x 1,300,000 lbs SHL, 9 sheave crown grooved for 1 1/2" wire line

LEE C MOORE swing-up substructure, 30' floor height, 26' clear height, 1,000,000# rotary capacity with 800,000 # setback capacity

(2) OILWELL A-1700 PT triplex mud pump, rigged out with (2) GE 752's

ROSS HILL model 1400, 4 bay SCR (rebuilt)

CANRIG 500 ton top drive with drive house

NATIONAL IR 3080 Iron rough neck

OILWELL 500 ton block with BJ 5500 Dynaplex hook

NATIONAL P-650 swivel

OILWELL 27 1/2" rotary table

KOOMEY 180 gal 7 station air and electric accumulator with remote

CHOKE MANIFOLD

(3) CATERPILLAR D399TA's each with KATO 1050 KW generators, cold start and wired

(3) Mud tanks with stirrers, shakers, electric centrifugal pumps, de sander, de silter, cyclone

10' x 45' pusher house

air compressors, trip tank, Oil bin, catwalk, driller dog house, ODS dog house, mixing house, fuel tank, derrick stand, water tanks, suitcases, survey unit, storage house and many extra's