

TRINCO[™] DRY BLAST EQUIPMENT MODEL 48X36/DP850-PC



- Ruggedly built of 14 Gauge welded steel
- Double floor 1/8" Expandex steel plus carbon screen
- Tungsten carbide nozzle
- Fluorescent lighting to eliminate shadows and minimize energy usage
- Large 12"x24" Safety glass window for excellent visibility and increased operator efficiency

CABINET SPECIFICATIONS:

Inside Depth:	36"
Width:	48"
Height:	36"
Overall Depth:	37"
Width:	53"
Height:	78"
Door Openings:	(2) Side Doors
Width:	28"
Height:	30"
Weight:	500 Lbs.

DP850 PRESSURE UNIT SPECIFICATIONS:

Overall Depth: 64" Width: 40" Height: 100" Weight: 900 Lbs

EQUIPMENT FEATURES:

- Abrasive separator is constructed of 10 gauge welded steel for durability, and tunable for different media
- Dust collector is constructed of 14 Gauge steel
- ASME Coded pressure vessel with easy access clean out port, automatic sealing plunger, and pneumatic vibrator
- ¾" Piping
- 30-120 P.S.I. Pressure range
- Abrasive capacity 100 Lb.
- Vibrating particle screen in abrasive separator
- Includes:

Airline water filter Pressure regulator and gauge Safety enclosed foot pedal Neoprene blast gloves ½" I.D. Heavy duty blast nozzle Tungsten carbide nozzle ¼" I.D. Standard, 1/8", 3/16" and 5/16" optional

DUST COLLECTOR

- Pull through type dust collector with motor and impeller on "clean air side"
- Includes 30 tubular filter bags (145 Square feet surface area)

Manual bag shaker

ABRASIVE SEPARATOR

- Rated 850 CFM
- Motor : 2HP

3450 R.P.M. 230V, 1 Phase, 60 HZ

Authorized TRINCO[™] Distributor Sales, Installation, Replacement Parts & Service

SALES & SERVICE 2019 SANDYDALE LANE HOUSTON, TX 77039 PHONE 281.987.0700 FAX 281.987.0704 A Blast Equipment Sales and Service Company www.arrowindustrial.net CORPORATE OFFICE P.O. BOX 891983 OKLAHOMA CITY, OK 73189 PHONE 405.794.2708 FAX 405.794.2309