

37 MW 2007 New Siemens SGT500 Natural Gas Generator



Harnessing Energy for Life



Harnessing Energy for Life

Description & Additional Notes

EXCLUSIVELY FROM USP&E!

USP&E is selling: 37 MW 2007 New Siemens SGT500 Natural Gas Generator Turbine and Gearbox Only! (Alternator provided at Extra Cost)

60 Hz;

Units available: 2x - 18.5 MW per Unit

**Note that price is for Both Units

If you are like us, you read every day about how thousands of fast growth companies struggle to find energy generation that is affordable, reliable and available for immediate shipping and installation on a turnkey basis from a company that really understands the complexities of integration of balance of plant and other site infrastructure.

At USP&E, we have been in business now for over 20 years and have offices in 9 countries. But more importantly, WE ARE OBSESSED WITH EACH CLIENTS JOURNEY TO ENERGY SUSTAINABILITY & RELIABILITY AND ARE DRIVEN TO GUIDE EACH CLIENT TO SUCCESSFUL INTEGRATION OF THE BEST IN CLASS TECHNOLOGIES.

This is important and a huge differentiating factor for our clients because USP&E isn't the hero of our story, you are. We will do everything possible to make sure you are successful, and we have over 20 years of satisfied clients and meaningful, long-term client engagements that prove this out. The potential delays related to permitting, land access, shipping, etc must be dealt with head-on and with urgency. We have helped hundreds of companies like yours for over 20 years.



Harnessing Energy for Life

Description & Additional Notes

The process is really simple:

1. Quick, 30 min Engineering/Design Meeting so we Can understand Your project goals, timelines and budgets. ✓
2. Scope of work and supply to match our plants to what you need. ✓
3. Work together to finalise commercial and technical aspects into a contract and move forward with the project. ✓

Please remember, USP&E is not just an equipment broker. We are a GUIDE to energy project excellence. We offer full Engineering, Procurement, Construction and long-term O&M in over 190 countries around the world in order to make sure our client projects are a RESOUNDING success.

Some of the companies we are currently working with include the City of Neom, Barrick Gold, SPACE-X, Firefinch Gold, Kurdistan MOE, Ivanhoe Mining, Boogertman Partners, and Molo Graphite.

At USP&E, we understand how most companies struggle to find energy generation that is affordable, reliable and available for immediate shipping and installation on a turnkey basis. Your partner must be a company that really understands the complexities of integration of balance of plant and other site infrastructure, and not just be a broker. Ideally, your partner offers complete O&M and warranty support services. This is what we have been doing for over 20 years.



Harnessing Energy for Life

Description & Additional Notes

SGT-500 Industrial Gas Turbine

Power Generation: (ISO) 18.47 MW(e) Base Load, 19.38 MW(e) Peak Load

The Siemens SGT-500 industrial gas turbine is a highly dependable gas turbine with excellent fuel flexibility. It combines the reliability and robustness of an industrial design and low emission levels of the latest turbine technology for a wide variety of fuels and applications at low operational costs.

The SGT-500 gas turbine has been serving the industrial power generation segment for over 50 years. Introduced in 1955, the turbine was designed for heavy oil operation under tough conditions. It is used widely in industrial power generation, marine as well as oil and gas applications, whether onshore or offshore, floating or fixed.

Due to its large roomy combustors and low firing temperature, the SGT-500 has the capability to operate on a wide range of fuels. Experience includes gas and heavy fuel oils, naphtha, crude oil, high aromatic and hydrogen-rich gases, as well as gases with high content of sulfuric acid.

In addition, the combustor and fuel system have the potential for easy adaptation to

additional liquid and gaseous fuels, including the growing flora of environmentally friendly fuels. The SGT-500 can be equipped with several emissions reduction alternatives, including Dry Low Emissions (DLE) combustion.

Outstanding operational reliability

With world class start-up and operation reliability performance, the SGT-500 is an excellent solution for emergency power applications. Its low firing temperature contributes to an impressive maintenance program. At operation on full load the standard time between major overhauls is 80,000 hours. At 94 % load the interval can be extended to 160 000 hours, equal to 18 years of operation.





Harnessing Energy for Life

Description & Additional Notes

Technical specifications

Overview

- Power generation: 18.47 MW(e)
- Electrical efficiency: 32.9%
- Heat rate: 10,946 kJ/kWh (10,375 Btu/kWh)
- Power turbine speed: 3,600 rpm
- Compressor pressure ratio: 13:1
- Exhaust gas flow: 96.4 kg/s (212.6 lb/s)
- Exhaust temperature: 376°C (709°F)
- NO_x emissions (with DLE corrected to 15% O₂ dry)
 - Natural gas: ≤42 ppmV

Axial Compressor

- Two multi-stage (10 + 8 LP/HP) axial flow compressors
- Compressor rotors of bolted design
- Corrosion-coating available

Combustion

- 7 can-annular combustion chambers
- Conventional combustion system
 - Steam or water injection for emissions control and power augmentation
- Dry Low Emissions (DLE) combustion system option (gas only)

Turbine

- Two compressor turbines (1 + 2 HP/LP)
- Free power turbine of axial-flow design
- 3-stage 3,600 rpm turbine

Fuel System

- Natural gas - Liquid fuel - Dual fuel - Heavy fuel
 - Other fuel capability available on request
- Fuel-changeover capability at any load
- Load-rejection capability
- Fuel-supply pressure requirement: 18.0 bar(a) ±0.5 bar (261±7 psi(a))

Bearings

- Hydrodynamic radial- and thrust bearings of tilting pad type
- Vibration and temperature monitoring

Lubrication

- Lubricating oil tank integrated into gas turbine skid
- AC-driven auxiliary pump
- DC-driven emergency pump
- AC-driven lube oil pumps with DC backup
- Air- or water-cooled lube oil coolers

Gearbox

- Parallel-shaft gear of double helical design
- High-speed shaft 3,600 rpm (nominal speed for PG)
- Low-speed shaft 1,500 rpm (50 Hz) or 1,800 rpm (60 Hz)
- 4 radial bearings of sleeve type

Generator

- 4-pole design
- Rated voltage: 10.5 kV/11.0 kV/13.8 kV
- 50 Hz or 60 Hz
- Protection IP54
- PMG for excitation power supply
- Complies with IEC/EN 60034-1 standard

Starting

- Start and barring motor connected to the LP rotor via a ratchet coupling

Control System

- Siemens Simatic control system
- Distributed inputs/outputs



Harnessing Energy for Life

Description & Additional Notes

Gas turbine:

Key features

- Robust design – long engine life
- High availability/reliability
- Low fuel-gas pressure requirement
- No advanced sealings, resulting in minimal deterioration and maintained efficiency
- Dry Low Emissions (DLE) system option
- Low starting power (<160 kW)
- Fast start capability (~3 minutes)
- Dual-fuel
- Competitive with dual-fuel reciprocating technology
- Marine classified
- No methane slip

Maintenance

- Extremely low and predictable maintenance costs
- Easy on-site maintenance possible
 - complete modules can be swiftly exchanged
- Direct exchange of gas generator possible
 - Core can be air-freighted
- First overhaul after 40,000 hours (80,000 hours between major overhauls)
- Lease-engine availability for planned overhauls
- Online wash available
- Standardized concepts for time-based and cycle-based maintenance
- Staff training in operation and maintenance
- 24/7 Siemens support
- Remote diagnostics

Package:

Key features

- Compact layout
- State-of-the-art control system fulfills all requirements for control and safety
- Can easily communicate with other control systems
- DNV, LR and ABS certified packages
- Marine package with auxiliary drive system on lightweight frame
- FPSO package (Floating Production, Storage and Offloading) option
- ATEX package option

Cogeneration and combined cycle

The SGT-500 is easily adapted to any cogeneration or combined-cycle plant layout. It has very low environmental impact in both configurations. Thanks to high air flow, the SGT-500 has excellent steam-raising capability which yields high total efficiency in cogeneration.


In combined cycle, the SGT-500 has very high total efficiency independent of the fuel used. When using HFO (heavy fuel oil) the SGT-500 offers outstanding emission performance and half the maintenance cost compared to competing technologies.



SGT-500 standard power generation package

- | | |
|------------------------|------------------------|
| 1 AC generator | 5 Core engine |
| 2 Speed reduction gear | 6 Enclosure air inlet |
| 3 Combustion exhaust | 7 Combustion air inlet |
| 4 Enclosure air outlet | |

SGT-500 Performance




Nominal generator output and heat rate

Conditions/assumptions:

Fuel: Natural Gas LHV, 46,798 kJ/kg (20,118 Btu/lb)
 Altitude: Sea level
 Ambient pressure: 1,013 bar (a) (14.7 psi (a))
 Relative humidity: 60 %
 Inlet pressure loss: 5 mbar (2" H₂O)
 Outlet pressure loss: 5 mbar (2" H₂O)
 Fuel temperature: 5°C (41°F)

Diagram conversion factors:

To convert	To	Multiply by
°C	°F	(°C x 9/5) + 32
MJ/kWh	Btu	949




Nominal exhaust mass flow and temperature

Conditions/assumptions:

Fuel: Natural Gas LHV, 46,798 kJ/kg (20,118 Btu/lb)
 Altitude: Sea level
 Ambient pressure: 1,013 bar(a) (14.7 psi(a))
 Relative humidity: 60 %
 Inlet pressure loss: 5 mbar (2" H₂O)
 Outlet pressure loss: 5 mbar (2" H₂O)
 Fuel temperature: 5°C (41°F)

Diagram conversion factors:

To convert	To	Multiply by
°C	°F	(°C x 9/5) + 32



Supplementary-fired heat-recovery steam generation

Conditions/assumptions:

Fuel: Natural Gas LHV, 46,798 kJ/kg (20,118 Btu/lb)
 Altitude: Sea level
 Ambient pressure: 1,013 bar(a) (14.7 psi(a))
 Ambient temperature: 15°C (59°F)
 Relative humidity: 60 %
 Boiler pinch point: 8 K (14 F)
 Boiler approach point: 5 K (9 F)
 Inlet pressure loss: 5 mbar (2" H₂O)
 Outlet pressure loss: 25 mbar (10" H₂O)

Diagram conversion factors:

To convert	To	Multiply by
°C	°F	(°C x 9/5) + 32
kg/s	lb/s	2.2046
bar	psi	14.5

Specifications



Manufacturer	Siemens
Model	SGT500
Year	2007
Condition	new
Location	Asia
Price	\$9,200,000
Category	Natural Gas Generators
Subcategories	<ul style="list-style-type: none">10 - 99 MW
Stock Number	USP009558
Wattage	37 MW
Hours	New
Frequency	60 Hz
Fuel type	Natural Gas
Voltage	NA
Balance of Plant Available? (BOP)	-

Asset Images



- Images may be representative, and actuals can be supplied upon request.

Asset Images



- Images may be representative, and actuals can be supplied upon request.

Asset Images



- Images may be representative, and actuals can be supplied upon request.



Harnessing Energy for Life