

Specification Data Sheet | Model: 15ARTBLU-EU(W)



ABBI-DELUXE 1500 Ltr / 160 Ltr

A steel in steel U.N (United Nations) approved IBC (Intermediate Bulk Container) suitable for transporting diesel fuel on the highway. The ABBI is fully bunded to ensure environmental compliance with Pollution Prevention Guidelines (PPG2) and has a 160 litre plastic Diefexhaust fluid (DEF) tank and pump cabinet in the front end.

- Secure lockable access hatch to enclose pumping equipmen, (diesel pump end only).
- Direct access into the inner tank via inspection hatch for cleaning and inspection.
- Full load lifting eyes and 2-way forklift pockets for ease of handling.
- Diesel and DEF pump compartments separated to avoid cross contamination of liquids.
- Internal baffles for safe transportation and manoeuvring.

SPECIFICATION

Standard Tank Fittings: 3" and 2" Fill Cap : Contents Gauge : 1" Pump Feed : Pressure/ Vaccum Vent : Generator Feed & Return Optional
Generator Feed Ports : Pump Bracket : Inspection Cover : 160 Ltr DEF Tank in front cabinet

Capacity (Brim Full) Litres:	1500 (+ 160 DEF)	Weight Unladen (kg):	655
Capacity (Brim Full) Gallons:	330 (+ 35 DEF)	Weight Laden (kg):	2200*
Dimensions Length (mm):	2300	Design Approvals:	ADR / UN IBC
Dimensions Width (mm):	1410	Design Standards:	Bunded to COP Regulations (PPG2)
Dimensions Height (mm)	1280		

Notes

* Specific gravity of diesel taken as 0.9 for this calculation

European Community Design Registration Number 001391049-0001/001391049-0002

Revision Date: 05/11/2015

