

Capacity (KVA)	HV Taps (V)	HV connection	High voltage (V)	Low voltage (V)	HV bushing layout	Connection type	Impedance	Oil type	Winding type	Standard	Qty
1000	4368-4264-4160-4056-3952	Delta	4.16	480V/277	Loop	Dyn1	5.75%	Mineral oil	AL	IEEE Std C57.12.34	9
1500	4368-4264-4160-4056-3952	Delta	4.16	480V/277	Loop	Dyn1	5.75%	Mineral oil	AL	IEEE Std C57.12.34	9
2000	4368-4264-4160-4056-3952	Delta	4.16	480V/277	Loop	Dyn1	5.75%	Mineral oil	AL	IEEE Std C57.12.34	7
500	14400-13800-13200-12870-12470-12000-11500	Delta	13.2	480V/277	Loop	Dyn1	5.75%	Mineral oil	AL	IEEE Std C57.12.34	4
750	14400-13800-13200-12870-12470-12000-11500	Delta	12.47	480V/277	Loop	Dyn1	5.75%	Mineral oil	AL	IEEE Std C57.12.34	3
1000	14400-13800-13200-12870-12470-12000-11500	Delta	12.47	480V/277	Loop	Dyn1	5.75%	Mineral oil	AL	IEEE Std C57.12.34	4
1500	14400-13800-13200-12870-12470-12000-11500	Delta	12.47	480V/277	Loop	Dyn1	5.75%	Mineral oil	AL	IEEE Std C57.12.34	5
2000	14400-13800-13200-12870-12470-12000-11500	Delta	13.2	480V/277	Loop	Dyn1	5.75%	Mineral oil	AL	IEEE Std C57.12.34	1
2000	14400-13800-13200-12870-12470-12000-11500	Delta	13.2	480V/277	Loop	Dyn1	5.75%	Mineral oil	AL	IEEE Std C57.12.34	13
2550	14400-13800-13200-12870-12470-12000-11500	Delta	13.2	480V/277	Loop	Dyn1	5.75%	Mineral oil	AL	IEEE Std C57.12.34	9
2550	14400-13800-13200-12870-12470-12000-11500	Delta	13.2	480V/277	Loop	Dyn1	5.75%	Mineral oil	AL	IEEE Std C57.12.34	17
2550	26187-25564-24940-24317-23693	Delta	24.94	480V/277	Loop	Dyn1	6.00%	Mineral oil	AL	IEEE Std C57.12.34	11
3000	26190-25560-24940-24320-23690	Delta	24.94	480V/277	Loop	Dyn1	5.75%	Mineral oil	AL	IEEE Std C57.12.34	2
2550	36225-35362-34500-33638-32775	Delta	34.5	480V/277	Loop	Dyn1	5.75%	Mineral oil	AL	IEEE Std C57.12.34	1
3000	14400-13800-13200-12870-12470-12000-11500	Delta	12.47	480V/277	Loop	Dyn1	5.75%	Mineral oil	AL	IEEE Std C57.12.34	6