

### POWER OPERATED OFFICE GUILLOTINE EBA 435 A

CONVENIENT ELECTRIC GUILLOTINE WITH  
AUTOMATIC CLAMP AND 430 MM CUTTING LENGTH

#### STANDARD FEATURES

- *electro-mechanical blade and clamp drive*
- *optical cutting line with bright and durable LEDs*
- *blade from high quality steel*
- *automatic clamp*
- *spindle guided backgauge with hand crank*
- *digital measurement readout for backgauge positioning (cm or inches)*
- *spindle driven backgauge for precise positioning*
- *precision side lay*
- *adjustable blade guides*
- *table top version; as an option: stand or cabinet available at an extra cost*

#### SAFETY FEATURES „SCS“ (SAFETY CUTTING SYSTEM)

- *two-hand safety activation with repetition blocking and control for synchronous operation*
- *electrically secured, transparent front safety guard*
- *transparent safety cover on the rear table*
- *safety drive with integrated mechanical and electrical overrun security*
- *automatic blade and clamp return from any position*
- *disc brake for immediate blade stop*
- *24-volt-control*
- *main switch, safety lock and key*
- *blade changing device with covered cutting edge*
- *blade depth adjustment from the outside of the machine*
- *easy blade change from the front of the machine without removing covers*
- *cutting stick can be turned or replaced easily from the outside of the machine*
- *knocking-up device*



EBA 435 A  
with optional cabinet

TECHNICAL DATA	EBA 435 A
Cutting length in mm	430
Cutting height in mm	40
Insertion depth in mm	390
Front table depth in mm	230
Minimum cut in mm	35
Power connection in volts/Hz (other voltages available)	230 / 50
Motor capacity in kW	0.45
Dimensions W x D x H in mm	640 x 695 x 360 / 1055 <sup>1</sup> / 1080 <sup>2</sup>
Weight in kgs	85 / 95 <sup>1</sup> / 117 <sup>2</sup>

The technical data is approximate. Subject to change. 06/09

<sup>1</sup> with stand <sup>2</sup> with cabinet

