
## Ruffinatti TZ-40 SATINMATIC



## Sugar pulling machine TZ.40

This is a newly-designed automatic machine used for pulling boiled sugar on a teflon-treated, cooled horizontal table. Pulling is carried out by two teflon-treated, cooled arms, which move in a circle at right angles to the work surface. When the machine is started, these arms plunge into the sugar mass, while a third, retractable arm emerges from the centre of the table to hold the mass itself. At this point, the rotating arms begin the pulling operation. The moving arms operate at a rate of 80 rpm. By comparison with conventional systems, pulling times are considerably reduced. They can, what is more, be regulated by means of a timer, which automatically stops the machine when the selected period elapses.















Installation of a TZ.40 between an IM.30 batch kneader and an AL.60 batch feeder in the Candy Servomatic line will give you automation of the sugar pulling operation and hence a saving of labour costs.





## Technical data

Capacity:
boiled batches weighing
up to 40 kg.
Pulling time:
10-15 secs. per mass.
Drives:
one 10 HP motor
one 1,5 HP motor
Overall size:
width 1400 mm.
depth 1590 mm.
height 1610 mm.
Net weight:
about 1450 kg.



Ruffinatti S.A.S. 10141 - Torino (Italia) Via Cantalupo, 7 Tel. 33 13 91 - Telegr. Gioruffinatti