

A CLEARER VISION FOR THE PERFECT FINISH

Atlas HT

hot top roller laminator



HT1650

Maximum thickness print + board	50mm
Maximum working width	1710mm
Maximum film width	1650mm
Maximum diameter of film roll	23cm
Diameter of rollers	114mm max
No. of self locking shafts supplied	5 + 1 unwind shaft
Temperature of upper roller	20 - 140°C
Adjustable Speed m/min	from 0.3 to 6.3
Power	1800W
Voltage	230v/50-60Hz
Amperage	8A
Weight of machine only	260kg
Dimensions of machine	w 206 x d 82 x h 153
Warranty	One year

Hot top roller laminator

- Top roller temperature up to 140°C enabling the use of heat activated laminates
- Useful for pressure sensitive laminate applications
- Small footprint with robust and innovative design
- Work can be processed sheet to roll or roll to roll as standard
- Pivoting feed tray with safety interlock allows for speedy roll changing
- Strong single chassis construction has additional roll storage and is fitted with castors for ease of movement
- Programmable control panel allows for individual speed, temperature and pressure adjustments
- Safety features include laser eye protection at the nip and two emergency stops

Call 01582 562518
sales@encoremachinery.co.uk
www.encoremachinery.co.uk

encore
 Print & Finishing Equipment

