



A CLEARER VISION FOR THE PERFECT FINISH

# mini kote

desk-top roll fed encapsulation machine

The Mini Kote has been designed to meet the increasing requirements from offices, educational establishments and small printshops for high quality, problem free desktop encapsulation.


The Mini Kote is of robust hot shoe construction, reliable and simple to use. It offers a consistent high quality level of encapsulation that is well proven and ideal for most short run applications.



A CLEARER VISION FOR THE PERFECT FINISH

# mini kote

desk-top roll fed encapsulation machine




Handy safety blade with magnetic locator.



Heated shoes provide a rapid warm-up and consistent heat source for both high and low melt films.



Simple to use pushbuttons, which offer both pre-set and fully variable controls, allow optimum settings for temperature and speed.



Colour coded mandrels ensure that core grips always face the correct way to tension the film for a flat result.



A security lock is provided for multiple user sites such as schools, colleges and offices.



Cooling fans give a high quality finish.

Call 01582 562518  
sales@encoremachinery.co.uk  
www.encoremachinery.co.uk

**encore**  
Print & Finishing Equipment



## Mini Kote - Desk-top Roll Fed, Hot Shoe Encapsulator

| Specifications              |               |           |           |
|-----------------------------|---------------|-----------|-----------|
| Dimensions                  | H – 330mm     | W – 890mm | L – 480mm |
| Weight                      | 32kg          |           |           |
| Electrical requirements     | 240v, 13 amps |           |           |
| Core size                   | 25mm (1")     |           |           |
| Running temperature         | Up to 135°C   |           |           |
| Maximum recommended stock * | 1mm           |           |           |
| Maximum working width       | 685mm         |           |           |

\* We recommend the use of SoluS 125 or 250 low melt gloss film with 1mm thick stock

| Maximum roll lengths |      |
|----------------------|------|
| 35/42 micron         | 150m |
| 75 micron            | 100m |
| 125 micron           | 50m  |
| 250 micron           | 25m  |