



**SAMED INNOVAZIONI SRL**

---

by **REBORD®** machinery

**Semplicità  
nell'innovazione**

Sistemi per la fabbricazione di  
libri fotografici e scatole di lusso

**Simplicity  
into innovation**

Photo book systems and  
luxury packaging boxes

Company SAMED INNOVAZIONI is a family company and we are into the bookbinding and paper converting sector from more than 15 years. Into our Head office in Prato (PO) – close to Florence – ITALY, we project, upgrade, set up and test all our equipments, on our own drawings and Patent. The innovation of Company SAMED is into continuous Development, to satisfy our Customers' inquiries and, thanks to our flexible and exclusive systems into the sector, we are able to run particular luxury packaging boxes giving a great result to the product.

Photos give an idea of some particular sizes and, as per customer's fantasy joined to our systems, We can run the production as in automatic as in semi-automatic cycle, keeping the simplicity and Compactness that is our mark of distinction into the market.

Innovation is also the possibility to invest into a sole equipment that could run as Traditional book covers and photo-books as boxes, both with special sizes (for example "S" curved sides or "Windowed" particulars) our equipments only can run easily without any tool or substitution of mechanical part.

We take part to the most important Exhibitions into our sector, like:

**Simplicity  
into innovation**

DRUPA	<i>Germany</i>
Graphispag	<i>Spain</i>
Photokina	<i>Germany</i>
IPEX	<i>UK</i>
Pack Print	<i>Bangkok</i>
IPMEX	<i>Malaysia</i>
Expoprint	<i>São Paulo, Brazil</i>
Polygraphinter	<i>Russia</i>
Printing Expo	<i>Shanghai, China</i>
Print 2013	<i>Chicago, USA</i>
Printing South China	<i>Guangzhou, China</i>
etc.	

With our own booths or by our Agents' booth. Our equipments are well known everywhere and are present into all Countries of the World.

# Darix con Posizionatore Automatico Cartoni

\*\*\* Questa ditta viene fornita standard con la macchina. Si usa impostando la macchina in modo manuale, viene piazzata facilmente dall'operatore sul piano di lavoro e permette una grande flessibilità in caso di piccole lavorazioni in differenti formati, evitando perdite di tempo per settaggi macchina.


## Copertinatrice con Posizionatore Automatico Cartoni

Formato minimo (copertina aperta)	105 x 170 mm
Formato massimo (copertina aperta)	60 x 180 mm con disp. piccoli formati
Spessore minino cartone	460 x 1000 mm
Larghezza dorsino	1,5 mm
Rimbocco materiale di copertura	Min: 10 mm
Spessore massimo cartone	Min: 15 mm      Max: 30 mm
Tipi di materiali lavorabili	6 mm - Possibilità di alimentare differenti spessori di cartone allo stesso tempo
Spessore materiali di copertura	Textile, carta laminata, carta fotografica, finta pelle, PVC polyuretano.
Capacità vasca colla	Da 80 a-400 g/m2
Produzione	5 kg gelatina animale a caldo (colle vinilica solo x risguardo)
Ingombro esterno x export	Fino a 250 pezzi (a seconda del formato e capacità operatore)
Peso netto macchina	220 x 200 x 180 cm (Lungh/Largh/Alt)
Peso lordo macchina	Kg 800
Alimentazione elettrica	Kg 900
Timer per il riscaldamento colla	400 Volts 3 fasi 50/60 Hz
Assorbimento	Per programmare l'accensione o lo spegnimento della resistenza nella vasca colla
Aria compressa	3.5 Kw
Distanza minima fra i cartoni in assenza di dorsino	6 Bar 500 NL/H
Numero standard di cartoni	5 mm
Numero massimo di cartoni	3 (Cartone + dorsino + cartone)
Alimentazione cartoni - movimento azionato da pistoni ad aria compressa	Fino a 5 sezioni cartone anche con spessori diversi
Dima manuale x posizionamento cartoni	6 Bar 30 N/L
	Da usare iin caso di piccole quantità in diversi formati. ***

## With autom board feeder

Minimum size (open Case)	105 x 170 mm
Maximum size (open Case)	60 x 180 mm with special small size device
Minimum thickness of the board	460 x 1000 mm
Spine width	1,5 mm
Overlap covering material	Min: 10 mm
Maximum thickness of the board	Min: 15 mm      Max: 30 mm
Cover material types	6 mm -Possibility to work Different board thickness. On the same cover
Cover material thickness	Textile, laminated paper, photo paper, imitation leather, PVC polyurethane
Glue tank capacity	From 80 up to -400 g/m2
Productivity	5 kg Hot animal Glue (Cold glue for lining works)
Overall dimensions x export	Up to 250 pieces / hour (as per size and operator skillfulness)
Machine Net weight	220 x 200 x 180 cm (Lenght/Width/Height)
Machine Gross weight	Kg 800 c.a
Electrical Power	Kg 900 c.a.
Timer for glue heating	400 Volts 3 Phases 50/60 Hz
Power	To programme the switching ON/OFF of the glue heating
Compressed Air	3.5Kw
Minimum distance between board elements if the cover doesn't have a spine	6 Bar 500 NL/H
Standard number of elements	5 mm
Maximum number of elements	3 ( Board + spine + board)
Feeding movement actionned by air pistons	Up to 5 boards with different thickness
Manual card board device	6 Bar 30 N/L
	To set up on the machinery for short quantity runs, to avoid the setting up for autom. Feeder. ***

\*\*\* This device is given STANDARD with the machinery. The machinery must be set into manual mode (excluding the autom. Board feeder). This device is easily placed on the vacuum table from the operator and it assures a great flexibility to get small running in different sizes, avoiding any time loosing for machine setting.



#### OPTIONS ADDIZIONALI

- Dispositivo x piccoli formati 60 x 180 mm
- Luce centrale di riferimento
- kit x alimentare fino a 5 pcs cartoni (sul posiz. Autom)
- Macchina Extra Formato = 700 x 1000 mm
- Viscosimetro: Dispositivo per il controllo automatico della viscosità colla con programma computerizzato. Dispositivo completo di miscelatore colla, sensore livello colla e alimentazione automatica acqua computerizzata x assicurare una costante viscosità.

#### ADDITIONAL EQUIPMENT

- Module for small size covers 60 x 180 mm
- Central light for reference
- Kit to feed 5 board pieces (set up on autom board feeder)
- Extra size machine = 700 x 1000 mm
- Viscometer: device for the automatic control of the glue viscosity by computerized setting, complete of glue mixer, glue level sensor and autom. Water feeding to keep the glue viscosity


**Darix Standard**



**Darix Evolution**  
con Posizionatore Automatico Cartoni



**Darix Evolution**  
«Turbo»



**Darix Evolution Light**



**Darix**  
con Posizionatore  
Automatico Cartoni



**MM1**



**Pendix**





**Oscar 100**



**Photofast  
Cold glue**



**Photofast  
Hot melt**




**Kostanza**



**Bordino**



**Hektor**





**encore**

Print & Finishing Equipment



Call 01582 562518

[sales@encoremachinery.co.uk](mailto:sales@encoremachinery.co.uk)

[www.encoremachinery.co.uk](http://www.encoremachinery.co.uk)