

A CLEARER VISION FOR THE PERFECT FINISH

# Atlas HA

hot top roller laminator



## Hot top roller laminator

- Available in two widths: 165cm & 210cm
- Top roller temperature up to 60°C
- Useful for pressure sensitive laminate applications
- Small footprint with robust and innovative design
- Work can be processed sheet to roll or roll to roll as standard
- Pivoting feed tray with safety interlock allows for speedy roll changing
- Strong single chassis construction has additional roll storage and is fitted with castors for ease of movement
- Programmable control panel allows for individual speed, temperature and pressure adjustments
- Safety features include laser eye protection at the nip and two emergency stops

	HA1650	HA2100
Maximum thickness print + board	50mm	50mm
Maximum working width	1710mm	2160mm
Maximum film width	1650mm	2080mm
Maximum diameter of film roll	23cm	23cm
Diameter of rollers	114mm max	114mm max
No. of self locking shafts supplied	5 + 1 unwind shaft	5 + 1 unwind shaft
Temperature range	30 - 60°C	30 - 60°C
Adjustable Speed m/min	from 0.3 to 6.3	from 0.3 to 6.3
Power	1800W	1800W
Voltage	230v/50-60Hz	230v/50-60Hz
Amperage	8A	8A
Weight of machine only	210kg	257kg
Dimensions of machine	w 206 x d 82 x h 153	w 250 x d 82 x h 153
Warranty	One year	One year

Call 01582 562518  
[sales@encoremachinery.co.uk](mailto:sales@encoremachinery.co.uk)  
[www.encoremachinery.co.uk](http://www.encoremachinery.co.uk)