

# Marine waste heat recovery

## Exhaust gas economizers



Product	Aalborg XS-2V	Aalborg XS-7V	Aalborg XS-TC7A	Aalborg Micro
Engines	Main or auxiliary	Main or auxiliary	Auxiliary	Auxiliary
Medium	Steam	Steam	Steam	Steam
Capacity	0.5–5.0 t/h	0.5–5.0 t/h	0.5–5.0 t/h	0.2–3.0 t/h
Design	<ul style="list-style-type: none"> <li>• Cylindrical</li> <li>• Vertical</li> <li>• Bare smoke tubes</li> <li>• Dual inlet available</li> <li>• With steam space</li> </ul>	<ul style="list-style-type: none"> <li>• Cylindrical</li> <li>• Vertical</li> <li>• Bare smoke tubes</li> <li>• Dual inlet available</li> <li>• Without steam space</li> </ul>	<ul style="list-style-type: none"> <li>• Cylindrical</li> <li>• Vertical</li> <li>• Helix smoke tubes</li> <li>• Single inlet</li> <li>• Without steam space</li> </ul>	<ul style="list-style-type: none"> <li>• Cylindrical</li> <li>• Vertical</li> <li>• Coiled water tubes with fins</li> <li>• Single inlet</li> <li>• Built-in damper and soot blower</li> <li>• Without steam space</li> </ul>
Pressure	10 bar(g)	10 bar(g)	10 bar(g)	8 bar(g) – higher upon request