

The Digitran System provides a complete sewing solution enabling you to sew your SEG as well as an array of digitral textiles. The synchronized transport system for sewing makes it simple for your operators to handle small or large projects in one workspace area.

- · Provides framing solutions for SEG
- Transport system syncronized for accurate and precise flow of material handling and product finishing



Power Requirements: 208-240 Volts - Single Phase - 13 Amps

Power Consumption: 3Kw

Air Requirements: 90 PSI at 1 CFM

3,000 mm x 750 mm (118 x 29.5 inches) Conveyor:

Seam width: Sewing: Single or Double Lockstitch

Speed: up to 20m/min.

*actual speed depends on fabric and application

Dimensions: Width: 1,945 mm (76.5 inches)

Length: 3,000 mm (118 inches)

Height: 960 mm (37.75 inches)

Electrical Requirements: 230V/13AMP, Single Phase

- precise flow of material handling and product finishing
- 2. Hands free SEG cutting
- Programmable back stitch configuration and stitch cut for easy operational use
- Synchronized needle bar and feed for even stitching
- Needle cooling for faster sewing**
- 6. Multiple seam configuration for almost any type of job
- 7. Light aluminum frame for easy mobility around your facility
- 8. Easy to use touch controls
- 9. Driven roller for large graphics
- 10. Robust Durkopp Adler sewing machine for maximum up time

^{**} optional - can be added onto machine as an option